

# SAFETY DATA SHEET

Revision Date 09-Sep-2018

Version 5

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Code FRP002
Product Name Cobalt Alloy

Synonyms ATI 188™, ATI L605™, ATI 6230™

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Cobalt alloy product manufacture

Uses advised against

### 1.3. Details of the supplier of the safety data sheet

### **Manufacturer**

ATI, 1000 Six PPG Place, Pittsburgh, PA 15222 USA

### 1.4. Emergency telephone number

Emergency Telephone Chemtrec: +1-703-741-5970

# Section 2: HAZARDS IDENTIFICATION

This product is an article and, as such, does not present a hazard to human health by inhalation or ingestion.

# 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Oral	Category 4
Respiratory sensitisation	Category 1B
Skin sensitisation	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity — repeated exposure	Category 1
Chronic aquatic toxicity	Category 4

# 2.2. Label elements

# **Emergency Overview**

# Danger

#### Hazard statements

Harmful if swallowed

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause cancer

Suspected of damaging fertility or the unborn child

Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled

May cause long lasting harmful effects to aquatic life



**Appearance** Various massive product forms

Physical state Solid

**Odour** Odourless

### **Precautionary Statements - Prevention**

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear protective gloves

If skin irritation occurs: Get medical advice/attention

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# 2.3 Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

**Synonyms** ATI 188<sup>™</sup>, ATI L605<sup>™</sup>, ATI 6230<sup>™</sup>.

Chemical Name	EC No	CAS No	Weight-%
Cobalt	213-158-0	7440-48-4	47-57
Nickel	231-111-4	7440-02-0	11-24
Chromium	231-157-5	7440-47-3	21-24
Tungsten	231-143-9	7440-33-7	14-16
Iron	231-096-4	7439-89-6	0-3
Manganese	231-105-1	7439-96-5	0-2

# **Section 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**Inhalation** If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove

to fresh air and consult a qualified health professional.

**Skin Contact** In the case of skin irritation or allergic reactions see a doctor.

Eye contact In the case of particles coming in contact with eyes during processing, treat as with any

foreign object.

**Ingestion** Not an expected route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** May cause acute gastrointestinal effects if swallowed. May cause allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

# **Section 5: FIREFIGHTING MEASURES**

### 5.1. Extinguishing media

### Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl) or class D dry powder fire extinguisher.

#### Unsuitable extinguishing media

Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material

#### 5.2. Special hazards arising from the substance or mixture

Intense heat. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

Hazardous combustion products Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer.

### 5.3. Advice for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

### Section 6: ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

### Personal precautions

Use personal protective equipment as required.

#### For emergency responders

Use personal protective equipment as required.

#### 6.2. Environmental precautions

Not applicable to massive product.

# 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up**Not applicable to massive product.

### 6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

# **Section 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

### Advice on safe handling

WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

### **Storage Conditions**

Keep chips, turnings, dust, and other small particles away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

### Incompatible materials

Dissolves in hydrofluoric acid.

# 7.3. Specific end use(s)

# **Risk Management Methods (RMM)**

The information required is contained in this Safety Data Sheet.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Cobalt 7440-48-4	-	STEL: 0.3 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	-	TWA: 0.02 mg/m <sup>3</sup>	Skin
Nickel 7440-02-0	-	STEL: 1.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	Skin
Chromium 7440-47-3	TWA: 2 mg/m <sup>3</sup>	STEL: 1.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Tungsten 7440-33-7	-	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	-	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	-
Iron 7439-89-6	-	-	-	-	-
Manganese 7439-96-5	-	STEL: 1.5 mg/m³ TWA: 0.5 mg/m³	TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m³ TWA: 0.02 mg/m³ Ceiling / Peak: 1.6 mg/m³ Ceiling / Peak: 0.16 mg/m³ TWA: 0.5 mg/m³
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Cobalt 7440-48-4	-	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.01 mg/m <sup>3</sup>
Nickel 7440-02-0	-	TWA: 1.5 mg/m <sup>3</sup>	-	TWA: 1 mg/m³ TWA: 0.1 mg/m³	TWA: 0.05 mg/m <sup>3</sup>
Chromium 7440-47-3	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
Tungsten 7440-33-7	-	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	-	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Iron 7439-89-6	-	-	-	-	-
Manganese 7439-96-5	-	TWA: 0.2 mg/m <sup>3</sup>	-	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Cobalt 7440-48-4	Skin	Skin TWA: 0.05 mg/m³	STEL: 0.2 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> STEL: 0.06 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
Nickel 7440-02-0	-	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.25 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> STEL: 0.15 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
Chromium 7440-47-3	TWA: 2 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup> STEL: 1.5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Tungsten 7440-33-7	STEL 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m³ STEL: 10 mg/m³

Page 4/10

Iron 7439-89-6	-	-	-	-	-
Manganese 7439-96-5	STEL 2 mg/m³ TWA: 0.5 mg/m³	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.3 mg/m <sup>3</sup>	TWA: 1 mg/m³ TWA: 0.1 mg/m³ STEL: 3 ppm STEL: 0.3 mg/m³	TWA: 0.2 mg/m³ STEL: 3 mg/m³

**Derived No Effect Level (DNEL)**No DNELs are available for this product as a whole

**Predicted No Effect Concentration** 

No PNECs are available for this product as a whole.

(PNEC)

8.2. Exposure controls

**Engineering Controls** Avoid generation of uncontrolled particles.

Personal protective equipment

**Eye/face protection** When airborne particles may be present, appropriate eye protection is recommended. For

example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that

shield the eyes from particles.

**Skin and body protection** Fire/flame resistant/retardant clothing may be appropriate during hot work with the product.

Cut-resistant gloves and/or protective clothing may be appropriate when sharp surfaces are

present.

**Respiratory protection** When particulates/fumes/gases are generated and if exposure limits are exceeded or

irritation is experienced, proper approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminate concentrations. Respiratory protection must be provided in accordance with current local

regulations.

**Environmental exposure controls** Section 6: ACCIDENTAL RELEASE MEASURES.

# **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1. Information on basic physical and chemical properties

Physical state Solid

AppearanceVarious massive product formsOdourOdourlessColourmetallic, grey or SilverOdour thresholdNot applicable

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

oH .

Melting point/freezing point 1260-1430 °C 2300-2600 °F

Boiling point / boiling range - Flash point -

Evaporation rate - Not applicable

Flammability (solid, gas) - Product not flammable in the form as distributed,

flammable as finely divided particles or pieces

resulting from processing of this product

Flammability Limit in Air

Upper flammability limit: -

Lower flammability limit -

Vapour pressure-Not applicableVapour density-Not applicable

Specific Gravity 7-9
Water solubility Insoluble

Solubility(ies)
Partition coefficient
Autoignition temperature

Not applicable
Not applicable
Not applicable

Decomposition temperature - Not applicable
Kinematic viscosity - Not applicable
Dynamic viscosity - Not applicable
Not applicable
Not applicable

**Explosive properties**Not applicable **Oxidising properties**Not applicable

9.2. Other information

Softening point -

Molecular weight

VOC Content (%) Not applicable

Density - Bulk density -

# **Section 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

Not applicable .

### 10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

### 10.3. Possibility of hazardous reactions

#### Hazardous polymerisation

Hazardous polymerisation does not occur.

### **Possibility of Hazardous Reactions**

None under normal processing.

### 10.4. Conditions to avoid

Dust formation and dust accumulation:

#### 10.5. Incompatible materials

Dissolves in hydrofluoric acid.

#### 10.6. Hazardous decomposition products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer.

# Section 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

# **Product Information**

InhalationNot an expected route of exposure for product in massive form.Eye contactNot an expected route of exposure for product in massive form.

**Skin Contact** May cause sensitisation by skin contact.

**Ingestion** Not an expected route of exposure for product in massive form.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Cobalt	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L
Nickel	> 9000 mg/kg bw	-	> 10.2 mg/L
Chromium	> 3400 mg/kg bw	-	> 5.41 mg/L
Tungsten	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Iron	98,600 mg/kg bw	-	> 0.25 mg/L
Manganese	>2000 mg/kg bw	-	>5.14 mg/L

### Information on toxicological effects

Symptoms May cause sensitisation by skin contact. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. May cause acute gastrointestinal effects if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Harmful if swallowed. Cobalt-containing powders may be fatal if inhaled.

Skin corrosion/irritation Product not classified.

Serious eye damage/eye irritation Product not classified.

Sensitisation May cause sensitisation by skin contact. Cobalt-containing alloys may cause sensitization

by inhalation.

Germ cell mutagenicity Product not classified.

**Carcinogenicity** May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Cobalt	A3	Group 2A	Known	X
7440-48-4		Group 2B		
Nickel		Group 1	Known	X
7440-02-0		Group 2B	Reasonably Anticipated	
Chromium		Group 3		
7440-47-3		,		

**Reproductive toxicity** Possible risk of impaired fertility.

STOT - single exposure Product not classified.

**STOT - repeated exposure** Causes disorder and damage to the: Respiratory System.

**Aspiration hazard** Product not classified.

# **Section 12: ECOLOGICAL INFORMATION**

### 12.1. Toxicity

This product as shipped is classified for aquatic chronic toxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Cobalt	The 72 h EC50 of cobalt	The 96h LC50 of cobalt	The 3 h EC50 of cobalt	The 48 h LC50 of cobalt
	dichloride to	dichloride ranged from 1.5	dichloride for activated	dichloride ranged from
	Pseudokirchneriella	mg Co/L for Oncorhynchus	sludge was 120 mg of	0.61 mg Co/L for
	subcapitata was 144 ug of	mykiss to 85 mg Co/L for	Co/L.	Ceriodaphnia dubia tested
	Co/L.	Danio rerio.		in soft, DOM-free water to
				>1800mg Co/L for Tubifex
				tubifex in very hard water.
Nickel	NOEC/EC10 values range	The 96h LC50s values	The 30 min EC50 of nickel	The 48h LC50s values
	from 12.3 µg/l for	range from 0.4 mg Ni/L for	for activated sludge was	range from 0.013 mg Ni/L
	Scenedesmus	Pimephales promelas to	33 mg Ni/L.	for Ceriodaphnia dubia to
	accuminatus to 425 µg/l for	320 mg Ni/L for		4970 mg Ni/L for Daphnia
	Pseudokirchneriella	Brachydanio rerio.		magna.
	subcapitata.			
Chromium	-	-	-	-
Tungsten	The 72 h EC50 of sodium	The 96 h LC50 of sodium	The 30 min EC50 of	The 48 h EC50 of sodium
	tungstate to	tungstate to Danio rerio	sodium tungstate for	tungstate to Daphnia
	Pseudokirchnerella	was greater than 106 mg	activated sludge were	magna was greater than
	subcapitata was 31.0 mg	of W/L.	greater than 1000 mg/L.	96 mg of W/L.
	of W/L.			
Iron	-	The 96 h LC50 of 50% iron	The 3 h EC50 of iron oxide	The 48 h EC50 of iron

		oxide black in water to	for activated sludge was	oxide to Daphnia magna
		Danio rerio was greater	greater than 10,000 mg/L.	was greater than 100
		than 10,000 mg/L.		mg/L.
Manganese	The 72 h EC50 of	The 96 h LC50 of	The 3 h EC50 of	The 48 h EC50 of
_	manganese to	manganese to	manganese for activated	manganese to Daphnia
	Desmodesmus	Oncorhynchus mykiss was	sludge was greater than	magna was greater than
	subspicatus was 2.8 mg of	greater than 3.6 mg of	1000 mg/L.	1.6 mg/L.
	Mn/L.	Mn/L	_	-

# 12.2. Persistence and degradability

.

# 12.3. Bioaccumulative potential

.

# 12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

The PBT and vPvB criteria do not apply to inorganic substances.

### 12.6. Other adverse effects

This product as shipped is not classified for acute environmental endpoints. However, when subjected to sawing or grinding, particles may be generated that are classified for aquatic acute toxicity

# **Section 13: DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

Waste from residues/unused

products

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging None anticipated.

# **Section 14: TRANSPORT INFORMATION**

# <u>IMDG</u>

14.1	UN/ID no	Not regulated
14.2	Proper shipping name	Not regulated
14.3	Hazard Class	Not regulated
14.4	Packing Group	Not regulated
14.5	Marine pollutant	Not applicable
14.6	Special Provisions	None
147	Transport in hulk according to	Not applicable

**14.7 Transport in bulk according to** Not applicable

Annex II of MARPOL and the IBC

Code

# <u>RID</u>

ted
ted
ted
ted
able
1

# ADR

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated

14.4	Packing Group	Not regulated
14.5	<b>Environmental hazard</b>	Not applicable

14.6 Special Provisions None

ICAO (air)

14.1 UN/ID noNot regulated14.2 Proper shipping nameNot regulated14.3 Hazard ClassNot regulated14.4 Packing GroupNot applicable14.5 Environmental hazardNot applicable

14.6 Special Provisions None

**IATA** 

14.1UN/ID noNot regulated14.2Proper shipping nameNot regulated14.3Hazard ClassNot regulated14.4Packing GroupNot regulatedDescriptionNot applicable14.5Environmental hazardNot applicable

14.6 Special Provisions None

# **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Cobalt	RG 65,RG 70,RG 70bis,RG	-
7440-48-4	70ter	
Nickel	RG 37ter	-
7440-02-0		
Chromium	RG 10	-
7440-47-3		
Tungsten	-	-
7440-33-7		
Iron	RG 44,RG 44bis,RG 94	-
7439-89-6		
Manganese	-	-
7439-96-5		

# **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

# Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV). This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### **International Inventories**

Complies **TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS IECSC** Complies Complies **KECL PICCS** Complies Complies **AICS** 

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### 15.2. Chemical safety assessment

No chemical safety assessment has been performed for this product.

# **Section 16: OTHER INFORMATION**

Issue Date 28-May-2015

Revision Date 09-Sep-2018

**Revision Note** Updated Section(s): 5, 7, 9, 15.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Note

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Additional information available from:

Safety data sheets and labels available at ATImetals.com

Page 10 / 10