



SAFETY DATA SHEET

Issue Date 28-May-2015

Revision Date 02-Jul-2024

Version 9

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code PM003
Product Name Nickel Alloy Powder

Synonyms Nickel Alloy Powder, including but not limited to: ATI 249™ Powder, ATI N625 PM™ Powder, ATI 40Ti PM™ Powder, ATI 45Ti PM™ Powder, Alloy 600 Powder, Alloy 690 Powder, and MISC-N Powder

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Alloy product manufacture

Uses advised against

1.3. Details of the supplier of the safety data sheet

Manufacturer

ATI Specialty Materials, 2020 Ashcraft Avenue, Monroe, NC 28110 USA

Contact Point ATI SDS Manager: +1-412-225-4911

1.4. Emergency telephone number

Emergency Telephone Chemtrec: +1-703-741-5970

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity — repeated exposure	Category 1
Chronic aquatic toxicity	Category 3

2.2. Label elements

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction

Suspected of causing cancer

Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled

Harmful to aquatic life with long lasting effects

**Appearance** Powder**Physical state** Solid**Odour** Odourless**Precautionary Statements - Prevention**

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wear protective gloves

Avoid breathing dust/fume

Avoid release to the environment

Precautionary Statements - Response

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3 Hazards not otherwise classified (HNOC)

Not applicable

Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:

Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus

cancer. Vanadium pentoxide (V₂O₅) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances**Synonyms**

Nickel Alloy Powder, including but not limited to: ATI 249™ Powder, ATI N625 PM™ Powder, ATI 40Ti PM™ Powder, ATI 45Ti PM™ Powder, Alloy 600 Powder, Alloy 690 Powder, and MISC-N Powder.

Chemical Name	EC No	CAS No	Weight-%
Nickel	231-111-4	7440-02-0	49 - <100
Titanium	231-142-3	7440-32-6	0 - 46
Chromium	231-157-5	7440-47-3	0 - 32
Iron	231-096-4	7439-89-6	0 - 21
Molybdenum	231-107-2	7439-98-7	0 - 20
Tungsten	231-143-9	7440-33-7	0 - 10
Vanadium	231-171-1	7440-62-2	0 - 7
Niobium	231-113-5	7440-03-1	0 - 6
Aluminium	231-072-3	7429-90-5	0 - 5.5
Tantalum	231-135-5	7440-25-7	0 - 5
Silicon	231-130-8	7440-21-3	0 - 3
Carbon	231-153-3	7440-44-0	0 - 2
Boron	231-151-2	7440-42-8	0 - 2
Manganese	231-105-1	7439-96-5	0 - 1

Hafnium	231-166-4	7440-58-6	0 - 1
Cobalt	213-158-0	7440-48-4	0 - <0.1

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation	If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove to fresh air and consult a qualified health professional.
Skin Contact	In the case of skin allergic reactions see a doctor. Wash off immediately with soap and plenty of water.
Eye contact	In the case of particles coming in contact with eyes during processing, treat as with any foreign object.
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergic skin reaction.
-----------------	-----------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl).

Unsuitable extinguishing media

Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material

5.2. Special hazards arising from the substance or mixture

Intense heat. Very fine, high surface area material resulting from processing this product may ignite spontaneously at room temperature WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard

Hazardous combustion products Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Vanadium pentoxide (V₂O₅) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

5.3. Advice for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment as required.

For emergency responders

Use personal protective equipment as required. Follow Emergency Response Guidebook, Guide No. 171, EXCEPT for FIRE follow Emergency Response Guidebook, Guide No. 170.

6.2. Environmental precautions

Collect spillage to prevent release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Sweep or shovel material into dry containers. Avoid creating uncontrolled dust.

6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

7.3. Specific end use(s)

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Nickel 7440-02-0	-	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³	Skin
Titanium 7440-32-6	-	-	-	-	-
Chromium 7440-47-3	TWA: 2 mg/m ³	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Iron 7439-89-6	-	-	-	-	-
Molybdenum 7439-98-7	-	-	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-

Tungsten 7440-33-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-
Vanadium 7440-62-2	-	-	-	-	Skin
Niobium 7440-03-1	-	-	-	-	-
Aluminium 7429-90-5	-	STEL: 30 mg/m ³ STEL: 12 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³
Tantalum 7440-25-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³
Silicon 7440-21-3	-	STEL: 30 ppm STEL: 12 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³	-	-
Carbon 7440-44-0	-	-	-	-	-
Boron 7440-42-8	-	-	-	-	-
Manganese 7439-96-5	-	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 1 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 0.02 mg/m ³ Ceiling / Peak: 1.6 mg/m ³ Ceiling / Peak: 0.16 mg/m ³ TWA: 0.5 mg/m ³
Hafnium 7440-58-6	-	-	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	-
Cobalt 7440-48-4	-	STEL: 0.3 mg/m ³ TWA: 0.1 mg/m ³	-	TWA: 0.02 mg/m ³	Skin
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Nickel 7440-02-0	-	TWA: 1.5 mg/m ³	-	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³
Titanium 7440-32-6	-	-	-	-	-
Chromium 7440-47-3	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³
Iron 7439-89-6	-	-	-	-	-
Molybdenum 7439-98-7	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-	TWA: 0.5 mg/m ³	-
Tungsten 7440-33-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Vanadium 7440-62-2	-	-	-	-	-
Niobium 7440-03-1	-	-	-	-	TWA: 5 mg/m ³ TWA: 0.5 mg/m ³
Aluminium 7429-90-5	-	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 0.05 mg/m ³	TWA: 1.5 mg/m ³	TWA: 5 mg/m ³ TWA: 2 mg/m ³
Tantalum 7440-25-7	-	TWA: 5 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Silicon 7440-21-3	-	-	-	-	TWA: 10 mg/m ³
Carbon 7440-44-0	-	-	-	-	-
Boron 7440-42-8	-	-	-	-	-
Manganese 7439-96-5	-	TWA: 0.2 mg/m ³	-	TWA: 0.2 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 0.1 mg/m ³
Hafnium 7440-58-6	-	TWA: 0.5 mg/m ³	-	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³
Cobalt 7440-48-4	-	TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³	TWA: 0.01 mg/m ³
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Nickel 7440-02-0	-	TWA: 0.5 mg/m ³	TWA: 0.25 mg/m ³	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.5 mg/m ³

Titanium 7440-32-6	-	-	STEL: 30 mg/m ³ TWA: 10 mg/m ³	-	-
Chromium 7440-47-3	TWA: 2 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ STEL: 1.5 mg/m ³	TWA: 2 mg/m ³
Iron 7439-89-6	-	-	-	-	-
Molybdenum 7439-98-7	STEL 20 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³	STEL: 10 mg/m ³ TWA: 4 mg/m ³	-	TWA: 0.5 mg/m ³
Tungsten 7440-33-7	STEL 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³
Vanadium 7440-62-2	STEL 1 mg/m ³ TWA: 0.5 mg/m ³	-	-	TWA: 0.2 mg/m ³ Ceiling: 0.05 mg/m ³ STEL: 0.6 mg/m ³	-
Niobium 7440-03-1	STEL 10 mg/m ³ STEL 1 mg/m ³ TWA: 5 mg/m ³ TWA: 0.5 mg/m ³	-	-	-	-
Aluminium 7429-90-5	STEL 20 mg/m ³ TWA: 10 mg/m ³	TWA: 3 mg/m ³	TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³
Tantalum 7440-25-7	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³
Silicon 7440-21-3	-	TWA: 3 mg/m ³	-	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³
Carbon 7440-44-0	-	-	-	-	-
Boron 7440-42-8	-	-	-	-	-
Manganese 7439-96-5	STEL 2 mg/m ³ TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.3 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³ STEL: 3 ppm STEL: 0.3 mg/m ³	TWA: 0.2 mg/m ³ STEL: 3 mg/m ³
Hafnium 7440-58-6	STEL 5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ STEL: 1.5 mg/m ³	TWA: 0.5 mg/m ³ STEL: 1.5 mg/m ³
Cobalt 7440-48-4	Skin	Skin TWA: 0.05 mg/m ³	STEL: 0.2 mg/m ³ TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³ STEL: 0.06 mg/m ³	TWA: 0.1 mg/m ³

Derived No Effect Level (DNEL) No DNELs are available for this product as a whole

Predicted No Effect Concentration (PNEC) No PNECs are available for this product as a whole.

8.2. Exposure controls

Engineering Controls Avoid generation of uncontrolled particles.

Personal protective equipment

Eye/face protection

When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that shield the eyes from particles.

Skin and body protection

Wear protective gloves. Fire/flame resistant/retardant clothing may be appropriate during hot work with the product.

Respiratory protection

When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminate concentrations. Respiratory protection must be provided in accordance with current local regulations.

Environmental exposure controls Section 6: ACCIDENTAL RELEASE MEASURES.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Solid

Appearance	Powder	Odour	Odourless
Colour	metallic grey or Silver	Odour threshold	Not applicable
Property	Values	Remarks • Method	
pH	-	Not applicable	
Melting point / freezing point	1400-1540 °C / 2560-2800 °F		
Boiling point / boiling range	-		
Flash point	-		
Evaporation rate	-	Not applicable	
Flammability (solid, gas)	-	Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product	
Flammability Limit in Air			
Upper flammability limit:		-	
Lower flammability limit		-	
Vapour pressure	-	Not applicable	
Vapour density	-	Not applicable	
Specific Gravity	8.0-8.5		
Water solubility	Insoluble		
Solubility(ies)			
Partition coefficient	-	Not applicable	
Autoignition temperature	-	Not applicable	
Decomposition temperature	-	Not applicable	
Kinematic viscosity	-	Not applicable	
Dynamic viscosity	-	Not applicable	
Explosive properties	Not applicable		
Oxidising properties	Not applicable		
9.2. Other information			
Softening point	-		
Molecular weight	-		
VOC Content (%)	Not applicable		
Density	-		
Bulk density	-		

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Hazardous polymerisation

Hazardous polymerisation does not occur.

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Dust formation and dust accumulation.

10.5. Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

10.6. Hazardous decomposition products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated: Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Vanadium pentoxide (V₂O₅) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Section 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Product Information**

Inhalation	Suspected of causing cancer by inhalation. Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled.
Eye contact	Product not classified.
Skin Contact	May cause sensitisation by skin contact.
Ingestion	Product not classified.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel	> 9000 mg/kg bw	-	> 10.2 mg/L
Titanium	> 5000 mg/kg bw	-	-
Chromium	> 3400 mg/kg bw	-	> 5.41 mg/L
Iron	98,600 mg/kg bw	-	> 0.25 mg/L
Molybdenum	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Tungsten	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Vanadium	> 2000 mg/kg bw	-	-
Niobium	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Aluminium	15,900 mg/kg bw	-	> 1 mg/L
Tantalum	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Silicon	> 5000 mg/kg bw	> 5000 mg/kg bw	> 2.08 mg/L
Carbon	> 2000 mg/kg bw	-	-
Boron	> 2000 mg/kg bw	-	> 5.08 mg/L
Manganese	>2000 mg/kg bw	-	>5.14 mg/L
Hafnium	> 5000 mg/kg bw	-	>4.3mg/L
Cobalt	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L

Information on toxicological effects

Symptoms May cause sensitisation by skin contact.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Product not classified.

Skin corrosion/irritation Product not classified.

Serious eye damage/eye irritation Product not classified.

Sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Product not classified.

Carcinogenicity Suspected of causing cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
---------------	-------	------	-----	------

Nickel 7440-02-0		Group 1 Group 2B	Known Reasonably Anticipated	X
Chromium 7440-47-3		Group 3		
Cobalt 7440-48-4	A3	Group 2A Group 2B	Known	X

Reproductive toxicity	Product not classified.
STOT - single exposure	Product not classified.
STOT - repeated exposure	Causes disorder and damage to the: Respiratory System.
Aspiration hazard	Product not classified.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

This product as shipped is classified for aquatic chronic toxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Nickel	NOEC/EC10 values range from 12.3 µg/l for <i>Scenedesmus accuminatus</i> to 425 µg/l for <i>Pseudokirchneriella subcapitata</i> .	The 96h LC50s values range from 0.4 mg Ni/L for <i>Pimephales promelas</i> to 320 mg Ni/L for <i>Brachydanio rerio</i> .	The 30 min EC50 of nickel for activated sludge was 33 mg Ni/L.	The 48h LC50s values range from 0.013 mg Ni/L for <i>Ceriodaphnia dubia</i> to 4970 mg Ni/L for <i>Daphnia magna</i> .
Titanium	The 72 h EC50 of titanium dioxide to <i>Pseudokirchnerella subcapitata</i> was 61 mg of TiO ₂ /L.	The 96 h LC50 of titanium dioxide to <i>Cyprinodon variegatus</i> was greater than 10,000 mg of TiO ₂ /L. The 96 h LC50 of titanium dioxide to <i>Pimephales promelas</i> was greater than 1,000 mg of TiO ₂ /L.	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of titanium dioxide to <i>Daphnia Magna</i> was greater than 1000 mg of TiO ₂ /L.
Chromium	-	-	-	-
Iron	-	The 96 h LC50 of 50% iron oxide black in water to <i>Danio rerio</i> was greater than 10,000 mg/L.	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L.	The 48 h EC50 of iron oxide to <i>Daphnia magna</i> was greater than 100 mg/L.
Molybdenum	The 72 h EC50 of sodium molybdate dihydrate to <i>Pseudokirchneriella subcapitata</i> was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to <i>Pimephales promelas</i> was 644.2 mg/L	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to <i>Ceriodaphnia dubia</i> was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to <i>Daphnia magna</i> was greater than 1,727.8 mg/L.
Tungsten	The 72 h EC50 of sodium tungstate to <i>Pseudokirchnerella subcapitata</i> was 31.0 mg of W/L.	The 96 h LC50 of sodium tungstate to <i>Danio rerio</i> was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of sodium tungstate to <i>Daphnia magna</i> was greater than 96 mg of W/L.
Vanadium	The 72 h EC50 of vanadium pentoxide to <i>Desmodesmus subspicatus</i> was 2,907 µg of V/L.	The 96 h LC50 of vanadium pentoxide to <i>Pimephales promelas</i> was 1,850 µg of V/L.	The 3 h EC50 of sodium metavanadate for activated sludge was greater than 100 mg/L.	The 48 h EC50 of sodium vanadate to <i>Daphnia magna</i> was 2,661 µg of V/L.
Niobium	-	-	-	-
Aluminium	The 96-h EC50 values for reduction of biomass of <i>Pseudokirchneriella subcapitata</i> in AAP-Medium at pH 6, 7,	The 96 h LC50 of aluminum to <i>Oncorhynchus mykiss</i> was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH	-	The 48-hr LC50 for <i>Ceriodaphnia dubia</i> exposed to Aluminium chloride increased from 0.72 to greater than 99.6

	and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved Al.	7.5		mg/L with water hardness increasing from 25 to 200 mg/L.
Tantalum	-	-	-	-
Silicon	The 72 h EC50 of sodium metasilicate pentahydrate to <i>Pseudokirchnerella subcapitata</i> was greater than 250 mg/L.	-	-	-
Carbon	The 72 h EL50 of Carbon to <i>Pseudokirchnerella subcapitata</i> was greater than 100 mg/L.	The 96 h LL50 of Carbon in water to <i>Danio rerio</i> was greater than 100 mg/L.	The 3 h EC50 of Carbon for activated sludge was 1000 mg/L.	The 48 h EL50 of Carbon to <i>Daphnia magna</i> was greater than 100 mg/L.
Boron	The 72-h EC50 value for reduction of biomass of <i>Pseudokirchnerella subcapitata</i> exposed to Boric acid at pH 7.5 to 8.3 was 40.2 mg/L.	The 96-hr LC50 for <i>Pimephales promelas</i> exposed to Boric acid (82%)/borax (18%) mixture was 79.7 mg/L with water hardness of 91 mg/L and water pH of 8.0.	The 3 h NOEC of boric acid for activated sludge ranged from 17.5 to 20 mg/L.	The 48-hr LC50 for <i>Ceriodaphnia dubia</i> exposed to Boric acid/borax mixture ranged from 91 to 165 mg/L with pH ranging from 6.7 to 8.4.
Manganese	The 72 h EC50 of manganese to <i>Desmodesmus subspicatus</i> was 2.8 mg of Mn/L.	The 96 h LC50 of manganese to <i>Oncorhynchus mykiss</i> was greater than 3.6 mg of Mn/L.	The 3 h EC50 of manganese for activated sludge was greater than 1000 mg/L.	The 48 h EC50 of manganese to <i>Daphnia magna</i> was greater than 1.6 mg/L.
Hafnium	The 72 h EC50 of hafnium to <i>Pseudokirchnerella subcapitata</i> was greater than 8 µg of Hf/L (100% saturated solution).	The 96 h LC50 of Hafnium dioxide in water to <i>Danio rerio</i> was greater than the solubility limit of 0.007 mg Hf/L.	-	The 48 h EC50 of Hafnium dioxide to <i>Daphnia magna</i> was greater than the solubility limit of 0.007 mg Hf/L.
Cobalt	The 72 h EC50 of cobalt dichloride to <i>Pseudokirchnerella subcapitata</i> was 144 µg of Co/L.	The 96h LC50 of cobalt dichloride ranged from 1.5 mg Co/L for <i>Oncorhynchus mykiss</i> to 85 mg Co/L for <i>Danio rerio</i> .	The 3 h EC50 of cobalt dichloride for activated sludge was 120 mg of Co/L.	The 48 h LC50 of cobalt dichloride ranged from 0.61 mg Co/L for <i>Ceriodaphnia dubia</i> tested in soft, DOM-free water to >1800mg Co/L for <i>Tubifex tubifex</i> in very hard water.

12.2. Persistence and degradability**12.3. Bioaccumulative potential****12.4. Mobility in soil****12.5. Results of PBT and vPvB assessment**

The PBT and vPvB criteria do not apply to inorganic substances.

12.6. Other adverse effects

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods**Waste from residues/unused products**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Section 14: TRANSPORT INFORMATION

IMDG

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Marine pollutant	Not applicable
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

RID

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

ADR

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

ICAO (air)

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

IATA

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
Description	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Nickel 7440-02-0	RG 37ter	-
Titanium 7440-32-6	-	-
Chromium 7440-47-3	RG 10	-

Iron 7439-89-6	RG 44, RG 44bis, RG 94	-
Molybdenum 7439-98-7	-	-
Tungsten 7440-33-7	-	-
Vanadium 7440-62-2	RG 66	-
Niobium 7440-03-1	-	-
Aluminium 7429-90-5	RG 32 RG 16, RG 16bis	-
Tantalum 7440-25-7	-	-
Silicon 7440-21-3	-	-
Carbon 7440-44-0	-	-
Boron 7440-42-8	-	-
Manganese 7439-96-5	-	-
Hafnium 7440-58-6	-	-
Cobalt 7440-48-4	RG 65, RG 70, RG 70bis, RG 70ter	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV). This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Cobalt - 7440-48-4	Cobalt - 231-158-0	

International Inventories

DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Not Listed
AICS	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No chemical safety assessment has been performed for this product.

Section 16: OTHER INFORMATION

Issue Date 28-May-2015
Revision Date 02-Jul-2024
Revision Note SDS sections updated: 1, 2, 3, 5, 10.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Note:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Additional information available from: Safety data sheets and labels available at ATImaterials.com