

# SAFETY DATA SHEET

Revision Date 22-Mar-2019 Version 1

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

### 1.1. Product identifier

**Product Code** 

PM030 Product Name Nickel Chromium Alloy Non-Respirable Powder

Nickel Chromium Alloy Non-Respirable Powder: HX **Synonyms** 

Contains Cobalt, Nickel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Nickel alloy product manufacture

Uses advised against

1.3. Details of the supplier of the safety data sheet

**Manufacturer** 

ATI, 1000 Six PPG Place, Pittsburgh, PA 15222 USA

1.4. Emergency telephone number

**Emergency Telephone** Chemtrec: +1-703-741-5970

# Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Respiratory sensitisation	Category 1B
Skin sensitisation	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity — repeated exposure	Category 1
Chronic aquatic toxicity	Category 3

# 2.2. Label elements

### **Emergency Overview**

### Danger

#### Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause cancer

Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled

Harmful to aquatic life with long lasting effects



**Odour** Odourless Appearance Powder Physical state Solid

### **Precautionary Statements - Prevention**

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear protective gloves Avoid breathing dust/fume In case of inadequate ventilation wear respiratory protection

Avoid release to the environment

IF ON SKIN: Wash with plenty of soap and water

### **Precautionary Statements - Response**

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### 2.3 Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Titanium dioxide, an IARC Group 2B carcinogen, Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer, Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substances

### **Synonyms**

Nickel Chromium Alloy Non-Respirable Powder: HX.

Chemical Name	EC No	CAS No	Weight-%
Nickel	231-111-4	7440-02-0	45 - 70
Chromium	231-157-5	7440-47-3	15 - 30
Iron	231-096-4	7439-89-6	15 - 25
Molybdenum	231-107-2	7439-98-7	0 - 12
Cobalt	213-158-0	7440-48-4	0 - <2.5
Tungsten	231-143-9	7440-33-7	0 - 2
Silicon	231-130-8	7440-21-3	0 - 2
Manganese	231-105-1	7439-96-5	0 - 2
Titanium	231-142-3	7440-32-6	0 - 1
Phosphorus	231-768-7	7723-14-0	0 - 1
Niobium	231-113-5	7440-03-1	0 - 1
Copper	231-159-6	7440-50-8	0 - 1
Carbon	231-153-3	7440-44-0	0 - 1
Aluminium	231-072-3	7429-90-5	0 - 1

# **Section 4: FIRST AID MEASURES**

Page 2/12

Revision Date 22-Mar-2019

### 4.1. Description of first aid measures

**Inhalation** If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove

to fresh air and consult a qualified health professional. In the case of asthma symptoms or

breathing difficulties call a doctor.

Skin Contact In the case of skin allergic reactions see a doctor. Wash off immediately with soap and

plenty of water.

Eye contact In the case of particles coming in contact with eyes during processing, treat as with any

foreign object.

Ingestion IF SWALLOWED. Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** May cause allergic skin reaction. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

# **Section 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl) or class D dry powder fire extinguisher.

#### Unsuitable extinguishing media

Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material

### 5.2. Special hazards arising from the substance or mixture

Intense heat Very fine, high surface area material resulting from processing this product may ignite spontaneously at room temperature WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard

Hazardous combustion products Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI)
may cause lung, nasal, and/or sinus cancer. Soluble molybdenum compounds such as
molybdenum trioxide may cause lung irritation.

### 5.3. Advice for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

# Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

### **Personal precautions**

Use personal protective equipment as required.

### For emergency responders

Use personal protective equipment as required. Follow Emergency Response Guidebook, Guide No. 171, EXCEPT for FIRE follow Emergency Response Guidebook, Guide No. 170.

# 6.2. Environmental precautions

Collect spillage to prevent release to the environment.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Sweep or shovel material into dry containers. Avoid creating uncontrolled dust.

#### 6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

# **Section 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

### Advice on safe handling

Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice.

# 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

11.14.1161

# Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

#### 7.3. Specific end use(s)

### **Risk Management Methods (RMM)**

The information required is contained in this Safety Data Sheet.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

	Chemical Name	European Union	United Kingdom	France	Spain	Germany
	Nickel	-	STEL: 1.5 mg/m³	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	Skin
_	7440-02-0		TWA: 0.5 mg/m <sup>3</sup>			
	Chromium	TWA: 2 mg/m <sup>3</sup>	STEL: 1.5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
	7440-47-3		TWA: 0.5 mg/m <sup>3</sup>			
	Iron	-	-	-	-	-
	7439-89-6					
	Molybdenum	-	-	-	TWA: 10 mg/m <sup>3</sup>	-
	7439-98-7				TWA: 3 mg/m <sup>3</sup>	
	Cobalt	-	STEL: 0.3 mg/m <sup>3</sup>	-	TWA: 0.02 mg/m <sup>3</sup>	Skin
	7440-48-4		TWA: 0.1 mg/m <sup>3</sup>			
	Tungsten	-	STEL: 10 mg/m <sup>3</sup>	-	STEL: 10 mg/m <sup>3</sup>	-
	7440-33-7		TWA: 5 mg/m <sup>3</sup>		TWA: 5 mg/m <sup>3</sup>	
	Silicon	-	STEL: 30 ppm	TWA: 10 mg/m <sup>3</sup>	-	-
	7440-21-3		STEL: 12 mg/m <sup>3</sup>	<u> </u>		
			TWA: 10 mg/m <sup>3</sup>			
			TWA: 4 mg/m <sup>3</sup>			
	Manganese	-	STEL: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>
	7439-96-5		TWA: 0.5 mg/m <sup>3</sup>			TWA: 0.02 mg/m <sup>3</sup>

Page 4/12

\_\_\_\_\_

					Ceiling / Peak: 1.6 mg/m³
					Ceiling / Peak: 0.16 mg/m³
					TWA: 0.5 mg/m <sup>3</sup>
Titanium 7440-32-6	-	-	-	-	-
Phosphorus 7723-14-0	-	-	-	-	TWA: 0.01 mg/m³ Ceiling / Peak: 0.02 mg/m³
Niobium 7440-03-1	-	-	-	-	-
Copper 7440-50-8	-	STEL: 0.6 mg/m <sup>3</sup> STEL: 2 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m³ TWA: 1 mg/m³ STEL: 2 mg/m³	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.1 mg/m³ Ceiling / Peak: 0.2 mg/m³
Carbon 7440-44-0	-	-	-	-	-
Aluminium 7429-90-5	-	STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>	TWA: 10 mg/m³ TWA: 5 mg/m³	TWA: 10 mg/m³ TWA: 5 mg/m³	TWA: 4 mg/m <sup>3</sup> TWA: 1.5 mg/m <sup>3</sup>
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Nickel 7440-02-0	-	TWA: 1.5 mg/m <sup>3</sup>	-	TWA: 1 mg/m³ TWA: 0.1 mg/m³	TWA: 0.05 mg/m <sup>3</sup>
Chromium 7440-47-3	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
Iron 7439-89-6	-	-	-	-	-
Molybdenum 7439-98-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	-	TWA: 0.5 mg/m <sup>3</sup>	-
Cobalt 7440-48-4	-	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.01 mg/m <sup>3</sup>
Tungsten 7440-33-7	-	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	-	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Silicon 7440-21-3	-		-	-	TWA: 10 mg/m <sup>3</sup>
Manganese 7439-96-5	-	TWA: 0.2 mg/m <sup>3</sup>	-	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>
Titanium 7440-32-6	-	-	-	-	-
Phosphorus 7723-14-0	-	-	-	-	-
Niobium 7440-03-1	-	-	-	-	TWA: 5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>
Copper 7440-50-8	-	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 1 mg/m³ TWA: 0.1 mg/m³	TWA: 1.0 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>
Carbon 7440-44-0	-	-	-	-	-
Aluminium 7429-90-5	-	TWA: 10 mg/m³ TWA: 5 mg/m³	TWA: 0.05 mg/m <sup>3</sup>	TWA: 1.5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Nickel 7440-02-0	-	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.25 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> STEL: 0.15 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
Chromium 7440-47-3	TWA: 2 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup> STEL: 1.5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Iron 7439-89-6	-	-	-	-	-
Molybdenum 7439-98-7	STEL 20 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>	-	TWA: 0.5 mg/m <sup>3</sup>
Cobalt 7440-48-4	Skin	Skin TWA: 0.05 mg/m <sup>3</sup>	STEL: 0.2 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>	TWA: 0.02 mg/m <sup>3</sup> STEL: 0.06 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
Tungsten 7440-33-7	STEL 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
Silicon 7440-21-3	-	TWA: 3 mg/m <sup>3</sup>	-	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>
Manganese 7439-96-5	STEL 2 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.3 mg/m <sup>3</sup>	TWA: 1 mg/m³ TWA: 0.1 mg/m³	TWA: 0.2 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>

				STEL: 3 ppm STEL: 0.3 mg/m <sup>3</sup>	
Titanium 7440-32-6	-	-	STEL: 30 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	-	-
Phosphorus 7723-14-0	STEL 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	STEL: 0.02 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup>	-	-	-
Niobium 7440-03-1	STEL 10 mg/m <sup>3</sup> STEL 1 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>	-	-	-	-
Copper 7440-50-8	STEL 4 mg/m <sup>3</sup> STEL 0.4 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	STEL: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.1 mg/m³ TWA: 1 mg/m³ STEL: 0.3 mg/m³ STEL: 3 mg/m³	TWA: 0.2 mg/m³ TWA: 1 mg/m³ STEL: 2 mg/m³
Carbon 7440-44-0	-	-	-	-	-
Aluminium 7429-90-5	STEL 20 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup> TWA: 1.2 mg/m <sup>3</sup>	TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 1 mg/m³ TWA: 5 mg/m³

Derived No Effect Level (DNEL) No DNELs are available for this product as a whole

Predicted No Effect Concentration

(PNEC)

No PNECs are available for this product as a whole.

8.2. Exposure controls

**Engineering Controls** Avoid generation of uncontrolled particles.

Personal protective equipment

Eye/face protection

When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that

shield the eyes from particles.

Skin and body protection

Fire/flame resistant/retardant clothing may be appropriate during hot work with the product.

Wear protective gloves.

Respiratory protection

When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminate concentrations. Respiratory protection must be provided in accordance with current local

regulations.

**Environmental exposure controls** 

Section 6: ACCIDENTAL RELEASE MEASURES.

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical stateSolidAppearancePowderOdourOdourlessColourmetallic grey or SilverOdour thresholdNot applicable

PropertyValuesRemarks • MethodpH-Not applicableMelting point/freezing point1400-1540 °C / 2560-2800 °F

Boiling point / boiling range -

Flash point - Evaporation rate -

**Evaporation rate** - Not applicable

Flammability (solid, gas) - Product not flammable in the form as distributed, flammable as finely divided particles or pieces

resulting from processing of this product

Flammability Limit in Air
Upper flammability limit:

Lower flammability limit -

Vapour pressure-Not applicableVapour density-Not applicable

**Specific Gravity** 8.0 - 8.5Water solubility Insoluble

Solubility(ies)

**Partition coefficient** Not applicable **Autoignition temperature** Not applicable Not applicable **Decomposition temperature** Kinematic viscosity Not applicable Not applicable Dynamic viscosity

**Explosive properties** Not applicable Not applicable **Oxidising properties** 

9.2. Other information

Softening point

Molecular weight

**VOC Content (%)** Not applicable

**Density Bulk density** 

# **Section 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

Not applicable

### 10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

# 10.3. Possibility of hazardous reactions

#### Hazardous polymerisation

Hazardous polymerisation does not occur.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### 10.4. Conditions to avoid

Dust formation and dust accumulation.

### 10.5. Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

#### 10.6. Hazardous decomposition products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:. Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

# Section 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

# **Product Information**

**Inhalation** May cause cancer by inhalation. Causes damage to the respiratory tract through prolonged

or repeated exposure if inhaled. Cobalt-containing alloys may cause sensitization by

inhalation.

**Eye contact** Product not classified.

**Skin Contact** May cause sensitisation by skin contact.

**Ingestion** Product not classified.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel	> 9000 mg/kg bw	-	> 10.2 mg/L
Chromium	> 3400 mg/kg bw	-	> 5.41 mg/L
Iron	98,600 mg/kg bw	-	> 0.25 mg/L
Molybdenum	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Cobalt	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L
Tungsten	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Silicon	> 5000 mg/kg bw	> 5000 mg/kg bw	> 2.08 mg/L
Manganese	>2000 mg/kg bw	-	>5.14 mg/L
Titanium	> 5000 mg/kg bw	-	-
Phosphorus	Iron Phosphide LD50 > 2000 mg/kg	-	Iron phosphide LC50 > 5.75 mg/L
	bw		
Niobium	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Copper	481 mg/kg bw	>2000 mg/kg bw	>5.11 mg/L
Carbon	> 2000 mg/kg bw	-	-
Aluminium	15,900 mg/kg bw	-	> 1 mg/L

# Information on toxicological effects

Symptoms May cause sensitisation by skin contact. May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Cobalt-containing powders may be harmful if inhaled.

**Skin corrosion/irritation** Product not classified.

Serious eye damage/eye irritation Product not classified.

Sensitisation May cause sensitisation by skin contact. Cobalt-containing alloys may cause sensitization

by inhalation.

Germ cell mutagenicity Product not classified.

**Carcinogenicity** May cause cancer by inhalation.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel		Group 1	Known	X
7440-02-0		Group 2B	Reasonably Anticipated	
Chromium		Group 3		
7440-47-3		*		
Cobalt	A3	Group 2A	Known	X
7440-48-4		Group 2B		

**Reproductive toxicity** Product not classified.

STOT - single exposure Product not classified.

**STOT - repeated exposure**Causes disorder and damage to the: Respiratory System.

**Aspiration hazard** Product not classified.

# **Section 12: ECOLOGICAL INFORMATION**

12.1. Toxicity

\_\_\_\_\_

This product as shipped is classified for aquatic chronic toxicity.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
	NOEC/EC10 values range from 12.3 µg/l for Scenedesmus accuminatus to 425 µg/l for Pseudokirchneriella subcapitata.	The 96h LC50s values range from 0.4 mg Ni/L for Pimephales promelas to 320 mg Ni/L for Brachydanio rerio.	The 30 min EC50 of nickel for activated sludge was 33 mg Ni/L.	The 48h LC50s values range from 0.013 mg Ni/L for Ceriodaphnia dubia to 4970 mg Ni/L for Daphnia magna.
Chromium	-	<u>-</u>	-	<u>-</u>
Iron	-	The 96 h LC50 of 50% iron oxide black in water to Danio rerio was greater than 10,000 mg/L.	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L.	The 48 h EC50 of iron oxide to Daphnia magna was greater than 100 mg/L.
Molybdenum	The 72 h EC50 of sodium molybdate dihydrate to Pseudokirchneriella subcapitata was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to Pimephales promelas was 644.2 mg/L	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to Ceriodaphnia dubia was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to Daphnia magna was greater than 1,727.8 mg/L.
Cobalt	The 72 h EC50 of cobalt dichloride to Pseudokirchneriella subcapitata was 144 ug of Co/L.	The 96h LC50 of cobalt dichloride ranged from 1.5 mg Co/L for Oncorhynchus mykiss to 85 mg Co/L for Danio rerio.	Co/L.	The 48 h LC50 of cobalt dichloride ranged from 0.61 mg Co/L for Ceriodaphnia dubia tested in soft, DOM-free water to >1800mg Co/L for Tubifex tubifex in very hard water.
Tungsten	The 72 h EC50 of sodium tungstate to Pseudokirchnerella subcapitata was 31.0 mg of W/L.	The 96 h LC50 of sodium tungstate to Danio rerio was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of sodium tungstate to Daphnia magna was greater than 96 mg of W/L.
Silicon	The 72 h EC50 of sodium metasilicate pentahydrate to Pseudokirchnerella subcapitata was greater than 250 mg/L.	•	-	-
Manganese	The 72 h EC50 of manganese to Desmodesmus subspicatus was 2.8 mg of Mn/L.	The 96 h LC50 of manganese to Oncorhynchus mykiss was greater than 3.6 mg of Mn/L	The 3 h EC50 of manganese for activated sludge was greater than 1000 mg/L.	The 48 h EC50 of manganese to Daphnia magna was greater than 1.6 mg/L.
Titanium	The 72 h EC50 of titanium dioxide to Pseudokirchnerella subcapitata was 61 mg of TiO2/L.	The 96 h LC50 of titanium dioxide to Cyprinodon variegatus was greater than 10,000 mg of TiO2/L. The 96 h LC50 of titanium dioxide to Pimephales promelas was greater than 1,000 mg of TiO2/L.	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of titanium dioxide to Daphnia Magna was greater than 1000 mg of TiO2/L.
Phosphorus	-	-	The 3 h NOEC of Ferrophosphorus for activated sludge was 1,000 mg/L.	The 48 h EC50 of Iron Phosphide to Daphnia magna was greater than 0.03 mg/L.
Niobium	-	-	-	-
Copper	The 72 h EC50 values of copper chloride to Pseudokirchneriella subcapitata ranged between 30 µg/L (pH 7.02, hardness 250 mg/L CaCO3, DOC 1.95 mg/L) and 824 µg/L (pH 6.22, hardness 100 mg/L CaCO3, DOC 15.8 mg/L).	The 96-hr LC50 for Pimephales promelas exposed to Copper sulfate ranged from 256.2 to 38.4 ug/L with water hardness increasing from 45 to 255.7 mg/L.	The 24 h NOEC of copper chloride for activated sludge ranged from 0.32 to 0.64 mg of Cu/L.	The 48 h LC50 values for Daphnia magna exposed to copper in natural water ranged between 33.8 µg/L (pH 6.1, hardness 12.4 mg/L CaCO3, DOC 2.34 mg/L) and 792 µg/L (pH 7.35, hardness 139.7 mg/L CaCO3, DOC 22.8 mg/L).
Carbon	The 72 h EL50 of Carbon	The 96 h LL50 of Carbon	The 3 h EC50 of Carbon	The 48 h EL50 of Carbon

to Pseudokirchneriella subcapitata was greater than 100 mg/L.	in water to Danio rerio was greater than 100 mg/L.	for activated sludge was 1000 mg/L.	to Daphnia magna was greater than 100 mg/L.
The 96-h EC50 values for reduction of biomass of Pseudokirchneriella subcapitata in AAP-Medium at pH 6, 7, and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved AI.	aluminum to Oncorhynchus mykiss was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH 7.5	<u>-</u>	The 48-hr LC50 for Ceriodaphnia dubia exposed to Aluminium chloride increased from 0.72 to greater than 99.6 mg/L with water hardness increasing from 25 to 200 mg/L.

### 12.2. Persistence and degradability

.

# 12.3. Bioaccumulative potential

.

# 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

The PBT and vPvB criteria do not apply to inorganic substances.

### 12.6. Other adverse effects

# **Section 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

# **Section 14: TRANSPORT INFORMATION**

### **IMDG**

<b>14.1 UN/ID no</b> No	t regulated
14.2 Proper shipping name No	t regulated
14.3 Hazard Class No	t regulated
14.4 Packing Group No	t regulated
14.5 Marine pollutant No	t applicable
14.6 Special Provisions No	ne

14.7 Transport in bulk according to Not applicable

Annex II of MARPOL and the IBC

Code

# <u>RID</u>

14.1 UN/ID no	Not regulated
14.2 Proper shipping nam	e Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazar	d Not applicable
44 C Chaolal Dravialana	Nono

14.6 Special Provisions None

Α	D	R

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

### ICAO (air)

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not applicable
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

# IATA

<u> </u>	
14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
Description	•
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

# **Section 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Nickel 7440-02-0	RG 37ter	-
Chromium 7440-47-3	RG 10	-
Iron 7439-89-6	RG 44,RG 44bis,RG 94	-
Molybdenum 7439-98-7	-	-
Cobalt 7440-48-4	RG 65,RG 70,RG 70bis,RG 70ter	-
Tungsten 7440-33-7	-	-
Silicon 7440-21-3	-	-
Manganese 7439-96-5	-	-
Titanium 7440-32-6	-	-
Phosphorus 7723-14-0	RG 5	-
Niobium 7440-03-1	-	-
Copper 7440-50-8	-	-
Carbon 7440-44-0	-	-
Aluminium 7429-90-5	RG 32 RG 16,RG 16bis	-

# **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

#### Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV). This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

**International Inventories** 

DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Not Listed
AICS Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### 15.2. Chemical safety assessment

No chemical safety assessment has been performed for this product.

# **Section 16: OTHER INFORMATION**

**Issue Date** 22-Mar-2019

Revision Date 22-Mar-2019

Revision Note New Safety Data Sheet.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Note:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **End of Safety Data Sheet**

Additional information available Safety data sheets and labels available at ATImetals.com

from: