

SAFETY DATA SHEET

Revision Date 26-Aug-2025 Version 1

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code SAC075

Product Name Nickel Base Alloys

Synonyms Non-powder forms of A905L™ Alloy, ATI 10242™ Alloy, ATI 120™ Alloy, Rene 88DT, ATI

188™ Alloy, ATI 200™ Alloy, ATI 201™ Alloy, ATI 22™ Alloy, ATI 235™ Alloy, ATI 2535™ Alloy, ATI 2550™ Alloy, ATI 35N LoTi™ Alloy, ATI 35N™ Alloy, ATI 400™ Alloy, ATI 42™ Alloy, ATI 500 ZB™ Alloy, ATI 520™ Alloy, ATI 600™ Alloy, ATI 617™ Alloy, ATI 6230™ Alloy, ATI 625 Lo-Fe™ Alloy, ATI 625™ Alloy, ATI 690™ Alloy, ATI 700™ Alloy, ATI 706™ Alloy, ATI 718-OP® Alloy, ATI 718Plus® Alloy, ATI 718™ Alloy, ATI 720™ Alloy, ATI 800™ Alloy, ATI 805™ Alloy, ATI 825™ Alloy, ATI 901™ Alloy, ATI 903™ Alloy, ATI 909™ Alloy, ATI 925™ Alloy, ATI A286™ Alloy, ATI ASTROLOY™ Alloy, ATI C-263™ Alloy, ATI C-276™ Alloy, ATI Gator Waspaloy* Alloy (* a Trademark of Pratt & Whitney), ATI GTD-222™ Alloy, ATI HB-2™ Alloy, ATI HG™ Alloy, ATI HN™ Alloy, ATI HS™ Alloy, ATI HX™ Alloy, ATI K-500™ Alloy, ATI L-605™ Alloy, ATI M-252™ Alloy, ATI MOLY PERMALLOY™ Alloy, ATI N-90™ Alloy, ATI P-31™ Alloy, ATI PE-16™ Alloy, ATI R26™

PERMALLOY™ Alloy, ATI N-90™ Alloy, ATI P-31™ Alloy, ATI PE-16™ Alloy, ATI R26™ Alloy, ATI Super Waspaloy* Alloy (* a Trademark of Pratt & Whitney), ATI W-722™ Alloy, ATI X-750™ Alloy, ATI X-751™ Alloy, ATI X-849™ Alloy, Rene 41™ Alloy, Rene 65™ Alloy, RENE 88 DT Alloy, RR1000* (* a Trademark of Rolls-Royce plc), RR1073* (* a Trademark of Rolls-Royce plc), ATI A159™ Alloy, TJA-1537® Hi-Carb Alloy, TJA-1537®

Lo-Carb Alloy, Waspaloy* Alloy (* a Trademark of Pratt & Whitney)

Contains Cobalt, Nickel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Nickel alloy product manufacture

Uses advised against

1.3. Details of the supplier of the safety data sheet

Manufacturer

ATI Specialty Alloys & Components, 1600 Old Salem Rd NE, Albany, OR 97321 USA

Contact Point ATI SDS Manager: +1-412-225-4911

1.4. Emergency telephone number

Emergency Telephone Chemtrec: +1-703-741-5970

Section 2: HAZARDS IDENTIFICATION

This product is an article and, as such, does not present a hazard to human health by inhalation or ingestion.

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Oral	Category 4
Respiratory sensitisation	Category 1B
Skin sensitisation	Category 1

Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity — repeated exposure	Category 1
Chronic aquatic toxicity	Category 3

2.2. Label elements

Emergency Overview

Danger

Hazard statements

Harmful if swallowed

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause cancer

May damage fertility or the unborn child

Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled

Harmful to aquatic life with long lasting effects



Appearance Various massive product forms

Physical state Solid

Odour Odourless

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear protective gloves

If skin irritation or rash occurs: Get medical advice/attention

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3 Hazards not otherwise classified (HNOC)

Not applicable

Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Titanium dioxide, an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Zinc. copper, magnesium, or cadmium fumes may cause metal fume fever, Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms

Non-powder forms of A905L™ Alloy, ATI 10242™ Alloy, ATI 120™ Alloy, Rene 88DT, ATI 188[™] Alloy, ATI 200[™] Alloy, ATI 201[™] Alloy, ATI 22[™] Alloy, ATI 235[™] Alloy, ATI 2535[™] Alloy, ATI 35N LoTi[™] Alloy, ATI 35N[™] Alloy, ATI 400[™] Alloy, ATI 42[™] Alloy, ATI 500 ZB™ Alloy, ATI 520™ Alloy, ATI 600™ Alloy, ATI 617™ Alloy, ATI 6230™ Alloy, ATI 625 Lo-Fe™ Alloy, ATI 625™ Alloy, ATI 690™ Alloy, ATI 700™ Alloy, ATI 706™

Alloy, ATI 718-OP® Alloy, ATI 718Plus® Alloy, ATI 718™ Alloy, ATI 720™ Alloy, ATI 800™ Alloy, ATI 80A™ Alloy, ATI 825™ Alloy, ATI 901™ Alloy, ATI 903™ Alloy, ATI 909™ Alloy, ATI 925™ Alloy, ATI A286™ Alloy, ATI ASTROLOY™ Alloy, ATI C-263™ Alloy, ATI C-276™ Alloy, ATI Gator Waspaloy* Alloy (* a Trademark of Pratt & Whitney), ATI GTD-222™ Álloy, ATI HB-2™ Álloy, ATI HÖ™ Alloy, ATI HN™ Alloy, ATI HŠ™ Alloy, ATI HX™ Alloy, ATI K-500™ Alloy, ATI L-605™ Alloy, ATI M-252™ Alloy, ATI MOLY PERMALLOY™ Alloy, ATI N-90™ Alloy, ATI P-31™ Alloy, ATI PE-16™ Alloy, ATI R26™ Alloy, ATI Super Waspaloy* Alloy (* a Trademark of Pratt & Whitney), ATI W-722™ Alloy, ATI X-750™ Alloy, ATI X-751™ Alloy, ATI X-849™ Alloy, Rene 41™ Alloy, Rene 65™ Alloy, RENE 88 DT Alloy, RR1000* (* a Trademark of Rolls-Royce plc), RR1073* (* a Trademark of Rolls-Royce plc), ATI A159™ Alloy, TJA-1537® Hi-Carb Alloy, TJA-1537® Lo-Carb Alloy, Waspaloy* Alloy (* a Trademark of Pratt & Whitney).

Chemical Name	EC No	CAS No	Weight-%
Nickel	231-111-4	7440-02-0	30 - 100
Iron	231-096-4	7439-89-6	0 - 42
Cobalt	213-158-0	7440-48-4	0 - 37
Copper	231-159-6	7440-50-8	0 - 35
Chromium	231-157-5	7440-47-3	0 - 35
Molybdenum	231-107-2	7439-98-7	0 - 26
Tungsten	231-143-9	7440-33-7	0 - 16
Niobium	231-113-5	7440-03-1	0 - 6
Titanium	231-142-3	7440-32-6	0 - 5
Tantalum	231-135-5	7440-25-7	0 - 5
Manganese	231-105-1	7439-96-5	0 - 5
Aluminium	231-072-3	7429-90-5	0 - 5

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove

to fresh air and consult a qualified health professional.

Skin Contact In the case of skin irritation or allergic reactions see a doctor.

Eve contact In the case of particles coming in contact with eyes during processing, treat as with any

foreign object.

Ingestion Not an expected route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction. May cause acute gastrointestinal effects if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl) or class D dry powder fire extinguisher.

Unsuitable extinguishing media

Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material

5.2. Special hazards arising from the substance or mixture

Intense heat. Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

Hazardous combustion products Titanium dioxide, an IARC Group 2B carcinogen, Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer, Zinc, copper, magnesium, or cadmium fumes may cause metal fume fever, Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

5.3. Advice for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protective equipment as required.

For emergency responders

Use personal protective equipment as required.

6.2. Environmental precautions

Not applicable to massive product.

6.3. Methods and material for containment and cleaning up

Methods for containment Not applicable to massive product.

Not applicable to massive product. Methods for cleaning up

6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimise combustible dust hazard.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep chips, turnings, dust, and other small particles away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

7.3. Specific end use(s)

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Nickel 7440-02-0	-	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³	Skin
Iron 7439-89-6	-	-	-	-	-
Cobalt 7440-48-4	-	STEL: 0.3 mg/m ³ TWA: 0.1 mg/m ³	-	TWA: 0.02 mg/m ³	Skin
Copper 7440-50-8	-	STEL: 0.6 mg/m³ STEL: 2 mg/m³ TWA: 0.2 mg/m³ TWA: 1 mg/m³	TWA: 0.2 mg/m³ TWA: 1 mg/m³ STEL: 2 mg/m³	TWA: 0.2 mg/m³ TWA: 1 mg/m³	TWA: 0.1 mg/m³ Ceiling / Peak: 0.2 mg/m³
Chromium 7440-47-3	TWA: 2 mg/m ³	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Molybdenum 7439-98-7	-	-	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-
Tungsten 7440-33-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-
Niobium 7440-03-1	-	-	-	-	-
Titanium 7440-32-6	-	-	-	-	-
Tantalum 7440-25-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³
Manganese 7439-96-5	-	STEL: 1.5 mg/m ³ TWA: 0.5 mg/m ³	TWA: 1 mg/m ³	TWA: 0.2 mg/m³	TWA: 0.2 mg/m³ TWA: 0.02 mg/m³ Ceiling / Peak: 1.6 mg/m³ Ceiling / Peak: 0.16 mg/m³ TWA: 0.5 mg/m³
Aluminium 7429-90-5	-	STEL: 30 mg/m ³ STEL: 12 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m³ TWA: 5 mg/m³	TWA: 4 mg/m³ TWA: 1.5 mg/m³
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
Nickel 7440-02-0	-	TWA: 1.5 mg/m ³	-	TWA: 1 mg/m³ TWA: 0.1 mg/m³	TWA: 0.05 mg/m ³
Iron 7439-89-6	-	-	-	-	-
Cobalt 7440-48-4	-	TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³	TWA: 0.01 mg/m ³
Copper 7440-50-8	-	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	TWA: 1.0 mg/m ³ TWA: 0.1 mg/m ³
Chromium 7440-47-3	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³
Molybdenum 7439-98-7	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-	TWA: 0.5 mg/m ³	-
Tungsten 7440-33-7	-	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Niobium 7440-03-1	-	-	-	-	TWA: 5 mg/m ³ TWA: 0.5 mg/m ³

Titanium 7440-32-6	-	-	-	-	-
Tantalum 7440-25-7	-	TWA: 5 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³
Manganese 7439-96-5	-	TWA: 0.2 mg/m ³	-	TWA: 0.2 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 0.1 mg/m ³
Aluminium 7429-90-5	-	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 0.05 mg/m ³	TWA: 1.5 mg/m ³	TWA: 5 mg/m ³ TWA: 2 mg/m ³
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
Nickel 7440-02-0	-	TWA: 0.5 mg/m ³	TWA: 0.25 mg/m ³	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.5 mg/m ³
Iron 7439-89-6	-	-	-	-	-
Cobalt 7440-48-4	Skin	Skin TWA: 0.05 mg/m ³	STEL: 0.2 mg/m ³ TWA: 0.02 mg/m ³	TWA: 0.02 mg/m ³ STEL: 0.06 mg/m ³	TWA: 0.1 mg/m ³
Copper 7440-50-8	STEL 4 mg/m ³ STEL 0.4 mg/m ³ TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	STEL: 0.2 mg/m³ TWA: 0.1 mg/m³	TWA: 0.2 mg/m ³	TWA: 0.1 mg/m ³ TWA: 1 mg/m ³ STEL: 0.3 mg/m ³ STEL: 3 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³ STEL: 2 mg/m ³
Chromium 7440-47-3	TWA: 2 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ STEL: 1.5 mg/m ³	TWA: 2 mg/m ³
Molybdenum 7439-98-7	STEL 20 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³	STEL: 10 mg/m ³ TWA: 4 mg/m ³	-	TWA: 0.5 mg/m ³
Tungsten 7440-33-7	STEL 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³
Niobium 7440-03-1	STEL 10 mg/m³ STEL 1 mg/m³ TWA: 5 mg/m³ TWA: 0.5 mg/m³	-	-	-	-
Titanium 7440-32-6	-	-	STEL: 30 mg/m ³ TWA: 10 mg/m ³	-	-
Tantalum 7440-25-7	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³
Manganese 7439-96-5	STEL 2 mg/m ³ TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.3 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³ STEL: 3 ppm STEL: 0.3 mg/m ³	TWA: 0.2 mg/m ³ STEL: 3 mg/m ³
Aluminium 7429-90-5	STEL 20 mg/m ³ TWA: 10 mg/m ³	TWA: 3 mg/m ³	TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 1 mg/m³ TWA mg/m³

No DNELs are available for this product as a whole **Derived No Effect Level (DNEL)**

(PNEC)

Predicted No Effect Concentration No PNECs are available for this product as a whole.

8.2. Exposure controls

Engineering Controls Avoid generation of uncontrolled particles.

Personal protective equipment

Eye/face protection

When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that

shield the eyes from particles.

Skin and body protection

Fire/flame resistant/retardant clothing may be appropriate during hot work with the product. Wear protective gloves. Cut-resistant gloves and/or protective clothing may be appropriate

when sharp surfaces are present.

Respiratory protection

When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminate concentrations. Respiratory protection must be provided in accordance with current local

regulations.

Environmental exposure controls

Section 6: ACCIDENTAL RELEASE MEASURES.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Solid

Appearance Various massive product forms Odour Odourless Colour metallic grey Silver **Odour threshold** Not applicable

Remarks • Method Property Values

рΗ Not applicable

1420 - 1450 °C / 2590 - 2650 °F Melting point / freezing point Boiling point / boiling range

Flash point

Evaporation rate

Not applicable Flammability (solid, gas) Product not flammable in the form as distributed.

flammable as finely divided particles or pieces resulting from processing of this product

Revision Date 26-Aug-2025

Flammability Limit in Air

Upper flammability limit: Lower flammability limit

Not applicable Vapour pressure Vapour density Not applicable

Specific Gravity 7-9 Water solubility Insoluble

Solubility(ies)

Not applicable **Partition coefficient** Not applicable **Autoignition temperature Decomposition temperature** Not applicable Kinematic viscosity Not applicable Dynamic viscosity Not applicable

Not applicable **Explosive properties Oxidising properties** Not applicable

9.2. Other information

Softening point Molecular weight

VOC Content (%) Not applicable

Density Bulk density

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Hazardous polymerisation

Hazardous polymerisation does not occur.

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Dust formation and dust accumulation.

10.5. Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

10.6. Hazardous decomposition products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Titanium dioxide, an IARC Group 2B carcinogen, Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer, Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

InhalationNot an expected route of exposure for product in massive form.Eye contactNot an expected route of exposure for product in massive form.

Skin Contact May cause sensitisation by skin contact.

Ingestion Not an expected route of exposure for product in massive form.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel	> 9000 mg/kg bw	-	> 10.2 mg/L
Iron	98,600 mg/kg bw	-	> 0.25 mg/L
Cobalt	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L
Copper	481 mg/kg bw	>2000 mg/kg bw	>5.11 mg/L
Chromium	> 3400 mg/kg bw	-	> 5.41 mg/L
Molybdenum	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Tungsten	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Niobium	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Titanium	> 5000 mg/kg bw	-	-
Tantalum	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Manganese	>2000 mg/kg bw	-	>5.14 mg/L
Aluminium	15,900 mg/kg bw	-	> 1 mg/L

Information on toxicological effects

Symptoms May cause sensitisation by skin contact. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. May cause acute gastrointestinal effects if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Harmful if swallowed. Cobalt-containing powders may be fatal if inhaled.

Skin corrosion/irritation Product not classified.

Serious eye damage/eye irritation Product not classified.

Sensitisation May cause sensitisation by skin contact. Cobalt-containing alloys may cause sensitization

by inhalation.

Germ cell mutagenicity Product not classified.

Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel		Group 1	Known	X
7440-02-0		Group 2B	Reasonably Anticipated	
Cobalt	A3	Group 2A	Known	X
7440-48-4		Group 2B		
Chromium		Group 3		
7440-47-3		·		

Reproductive toxicityContains a known or suspected reproductive toxin.

STOT - single exposure Product not classified.

STOT - repeated exposure Causes disorder and damage to the: Respiratory System.

Aspiration hazard Product not classified.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

This product as shipped is classified for aquatic chronic toxicity.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Nickel	NOEC/EC10 values range from 12.3 µg/l for	The 96h LC50s values range from 0.4 mg Ni/L	The 30 min EC50 of nickel for activated sludge was	The 48h LC50s values range from 0.013 mg Ni/L
	Scenedesmus accuminatus to 425 µg/l for Pseudokirchneriella subcapitata.	for Pimephales promelas to 320 mg Ni/L for Brachydanio rerio.	33 mg Ni/L.	for Ceriodaphnia dubia to 4970 mg Ni/L for Daphnia magna.
Iron	<u>-</u>	oxide black in water to Danio rerio was greater	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L.	The 48 h EC50 of iron oxide to Daphnia magna was greater than 100
Cobalt	The 72 h EC50 of cobalt dichloride to Pseudokirchneriella subcapitata was 144 ug of Co/L.	than 10,000 mg/L. The 96h LC50 of cobalt dichloride ranged from 1.5 mg Co/L for Oncorhynchus mykiss to 85 mg Co/L for Danio rerio.	The 3 h EC50 of cobalt dichloride for activated sludge was 120 mg of Co/L.	mg/L. The 48 h LC50 of cobalt dichloride ranged from 0.61 mg Co/L for Ceriodaphnia dubia tested in soft, DOM-free water to >1800mg Co/L for Tubifex tubifex in very hard water.
Copper	The 72 h EC50 values of copper chloride to Pseudokirchneriella subcapitata ranged between 30 µg/L (pH 7.02, hardness 250 mg/L CaCO3, DOC 1.95 mg/L) and 824 µg/L (pH 6.22, hardness 100 mg/L CaCO3, DOC 15.8 mg/L).	ranged from 256.2 to 38.4	The 24 h NOEC of copper chloride for activated sludge ranged from 0.32 to 0.64 mg of Cu/L.	The 48 h LC50 values for Daphnia magna exposed to copper in natural water ranged between 33.8 µg/L (pH 6.1, hardness 12.4 mg/L CaCO3, DOC 2.34 mg/L) and 792 µg/L (pH 7.35, hardness 139.7 mg/L CaCO3, DOC 22.8 mg/L).
Chromium Molybdenum	The 72 h EC50 of sodium molybdate dihydrate to Pseudokirchneriella subcapitata was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to Pimephales promelas was 644.2 mg/L	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to Ceriodaphnia dubia was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to Daphnia magna was greater than 1,727.8 mg/L.
Tungsten	The 72 h EC50 of sodium tungstate to Pseudokirchnerella subcapitata was 31.0 mg of W/L.	The 96 h LC50 of sodium tungstate to Danio rerio was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of sodium tungstate to Daphnia magna was greater than 96 mg of W/L.
Niobium	-	-	-	-

Titanium The 72 h EC50 of titanium The 96 h LC50 of titanium The 3 h EC50 of titanium The 48 h EC50 of titanium dioxide to dioxide to Cyprinodon dioxide for activated dioxide to Daphnia Magna Pseudokirchnerella variegatus was greater was greater than 1000 mg sludge were greater than than 10,000 mg of TiO2/L subcapitata was 61 mg of 1000 mg/L. of TiO2/L. TiO2/L. The 96 h LC50 of titanium dioxide to Pimephales promelas was greater thar 1,000 mg of TiO2/L Tantalum Manganese The 72 h EC50 of The 96 h LC50 of The 3 h EC50 of The 48 h EC50 of manganese to manganese to manganese for activated manganese to Daphnia Desmodesmus Oncorhynchus mykiss was sludge was greater than magna was greater than subspicatus was 2.8 mg of greater than 3.6 mg of 1000 mg/L. 1.6 mg/L. Mn/L Mn/L The 96-h EC50 values for The 96 h LC50 of Aluminium The 48-hr LC50 for reduction of biomass of aluminum to Ceriodaphnia dubia Pseudokirchneriella Oncorhynchus mykiss was exposed to Aluminium subcapitata in 7.4 mg of Al/L at pH 6.5 chloride increased from and 14.6 mg of Al/L at pH AAP-Medium at pH 6, 7, 0.72 to greater than 99.6 and 8 were estimated as mg/L with water hardness 20.1, 5.4, and 150.6 µg/L, increasing from 25 to 200 respectively, for dissolved mg/L. AI.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

The PBT and vPvB criteria do not apply to inorganic substances.

12.6. Other adverse effects

This product as shipped is not classified for acute environmental endpoints. However, when subjected to sawing or grinding, particles may be generated that are classified for aquatic acute toxicity

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging None anticipated.

Section 14: TRANSPORT INFORMATION

IMDG

14.1 UN/ID noNot regulated14.2 Proper shipping nameNot regulated14.3 Hazard ClassNot regulated14.4 Packing GroupNot regulated14.5 Marine pollutantNot applicable14.6 Special ProvisionsNone

14.7 Transport in bulk according to Not applicable

Annex II of MARPOL and the IBC Code

R	I	I)

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

<u>ADR</u>

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
Subsidiary hazard class	6.1
14.4 Packing Group	Not regulated

Not regulated 14.4 Packing Group 14.5 Environmental hazard Not applicable

14.6 Special Provisions None

ICAO (air)

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not applicable
14.5 Environmental hazard	Not applicable
440.0	N1

14.6 Special Provisions None

<u>IATA</u>

14.1 UN/ID no	Not regulated
14.2 Proper shipping name	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	Not regulated
Description	
14.5 Environmental hazard	Not applicable

ole

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
Nickel	RG 37ter	<u>-</u>
7440-02-0		
Iron	RG 44,RG 44bis,RG 94	-
7439-89-6		
Cobalt	RG 65,RG 70,RG 70bis,RG	<u>-</u>
7440-48-4	70ter	
Copper	-	-
7440-50-8		
Chromium	RG 10	-
7440-47-3		
Molybdenum	-	-
7439-98-7		
Tungsten	-	-
7440-33-7		
Niobium	-	-
7440-03-1		
Titanium	-	-
7440-32-6		
Tantalum	-	-
7440-25-7		

Manganese 7439-96-5	-	-
Aluminium 7429-90-5	RG 32 RG 16,RG 16bis	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV). This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

		Substance subject to authorisation per REACH Annex XIV
Cobalt - 7440-48-4	Cobalt - 231-158-0	

International Inventories

DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Not Listed
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No chemical safety assessment has been performed for this product.

Section 16: OTHER INFORMATION

Issue Date 26-Aug-2025

Revision Date 26-Aug-2025

Revision Note New Safety Data Sheet.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Note:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Additional information available Safety data sheets and labels available at ATImaterials.com

from: