

## SAFETY DATA SHEET

Issue Date 28-May-2015 Revision Date 23-Apr-2020 Version 5

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name Tantalum and Tantalum Alloys

Other means of identification

Product Code SAC003

Synonyms Tantalum and Tantalum Alloys: All solid (non-powder) Tantalum products, (Product #612)

Recommended use of the chemical and restrictions on use
Recommended Use
Alloy product manufacture.

Uses advised against

Details of the supplier of the safety data sheet

**Manufacturer Address** 

ATI, 1000 Six PPG Place, Pittsburgh, PA

15222 USA

Emergency telephone number

Emergency Telephone Chemtrec: 1-800-424-9300

#### 2. HAZARDS IDENTIFICATION

#### Classification

This material is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### Label elements

Emergency Overview		
Appearance Various massive product	Physical state Solid	Odor Odorless
forms	<b>,</b>	<b></b>

#### Hazards not otherwise classified (HNOC)

Not applicable

Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated: Titanium dioxide an IARC Group 2B carcinogen.

Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Synonyms** 

Tantalum and Tantalum Alloys: All solid (non-powder) Tantalum products, (Product #612).

Page 1/8

North America; English

Chemical Name	CAS No.	Weight-%
Tantalum	7440-25-7	60->99
Niobium (Columbium)	7440-03-1	0-35
Titanium	7440-32-6	0-25
Tungsten	7440-33-7	0-10
Vanadium	7440-62-2	0-10
Hafnium	7440-58-6	0-5

## 4. FIRST AID MEASURES

First aid measures

Eye contact In the case of particles coming in contact with eyes during processing, treat as with any

foreign object.

**Skin Contact** None under normal use conditions.

**Inhalation** If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove

to fresh air and consult a qualified health professional.

**Ingestion** Not an expected route of exposure.

Most important symptoms and effects, both acute and delayed

**Symptoms** None anticipated.

Indication of any immediate medical attention and special treatment needed

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl) or class D dry powder fire extinguisher.

Unsuitable extinguishing media Do not spray water on burning metal as an explosion may occur. This explosive

characteristic is caused by the hydrogen and steam generated by the reaction of water with

the burning material.

Specific hazards arising from the chemical

Intense heat. Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Hazardous combustion products Titanium dioxide an IARC Group 2B carcinogen. Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Page 2/8

\_\_\_\_\_\_

**Personal precautions**Use personal protective equipment as required.

For emergency responders

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Not applicable to massive product.

Methods and material for containment and cleaning up

Methods for containment

Not applicable to massive product.

Methods for cleaning up

Not applicable to massive product.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

Advice on safe handling Very fine, high surface area material resulting from grinding, buffing, polishing, or similar

processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep chips, turnings, dust, and other small particles away from heat, sparks, flame and

other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above

200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon

 $tetrachloride,\,carbon\,\,tetrafluoride,\,and\,\,freon.$ 

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Chemical Name	ACGIH TLV	OSHA PEL
Tantalum	-	TWA: 5 mg/m <sup>3</sup>
7440-25-7		_
Niobium (Columbium)	-	-
7440-03-1		
Titanium	-	-
7440-32-6		
Vanadium	-	Ceiling: 0.5 mg/m³ V2O5 respirable dust
7440-62-2		Ceiling: 0.1 mg/m <sup>3</sup> V2O5 fume
Tungsten	STEL: 10 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> W	(vacated) STEL: 10 mg/m³ (vacated) STEL:
7440-33-7	TWA: 5 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> W	10 mg/m <sup>3</sup> W
Hafnium	TWA: 0.5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> Hf	TWA: 0.5 mg/m <sup>3</sup>
7440-58-6		

## **Appropriate engineering controls**

**Engineering Controls** Avoid generation of uncontrolled particles.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** When airborne particles may be present, appropriate eye protection is recommended. For

example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that

shield the eyes from particles.

**Skin and body protection** Fire/flame resistant/retardant clothing may be appropriate during hot work with the product.

Cut-resistant gloves and/or protective clothing may be appropriate when sharp surfaces are

Page 3/8

present.

When particulates/fumes/gases are generated and if exposure limits are exceeded or Respiratory protection

irritation is experienced, proper approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local

Not applicable

Not applicable

Not applicable Not applicable

Not applicable

Not applicable

Not applicable

regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

**Physical state** 

**Appearance** Various massive product forms Odor Odorless Color blue gray Odor threshold Not applicable

Values Remarks • Method **Property** 

Not applicable pН Melting point / freezing point 2600-2800 °C / 4710-5070 °F

Boiling point / boiling range

Flash point **Evaporation rate** Not applicable

Product not flammable in the form as distributed, Flammability (solid, gas)

flammable as finely divided particles or pieces resulting from processing of this product

Flammability Limit in Air

Upper flammability limit: Lower flammability limit: Vapor pressure

Vapor density **Specific Gravity** 13.6-16.8

Water solubility Insoluble Solubility in other solvents

**Partition coefficient Autoignition temperature Decomposition temperature** Kinematic viscosity **Dvnamic viscosity** 

**Explosive properties** Not applicable Oxidizing properties Not applicable

**Other Information** 

Softening point

Molecular weight **VOC Content (%)** Not applicable

Density

**Bulk density** 850-1050 lb/ft3

## 10. STABILITY AND REACTIVITY

#### Reactivity

Not applicable

## **Chemical stability**

Stable under normal conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

\_\_\_\_\_

#### Hazardous polymerization

Hazardous polymerization does not occur.

#### Conditions to avoid

Dust formation and dust accumulation.

#### Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

#### **Hazardous Decomposition Products**

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated: Titanium dioxide an IARC Group 2B carcinogen. Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Not an expected route of exposure for product in massive form.

Eye contact Not an expected route of exposure for product in massive form.

Skin Contact Product not classified.

**Ingestion** Not an expected route of exposure for product in massive form.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tantalum 7440-25-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Niobium (Columbium) 7440-03-1	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Titanium 7440-32-6	> 5000 mg/kg bw	-	-
Vanadium 7440-62-2	> 2000 mg/kg bw	-	-
Tungsten 7440-33-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Hafnium 7440-58-6	> 5000 mg/kg bw	-	>4.3mg/L

#### Information on toxicological effects

Symptoms None known.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity
Skin corrosion/irritation
Serious eye damage/eye irritation
Sensitization
Germ cell mutagenicity
Carcinogenicity
Product not classified.

Reproductive toxicity Product not classified.
STOT - single exposure Product not classified.
STOT - repeated exposure Product not classified.
Aspiration hazard Product not classified.

Page 5/8

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

This product as shipped is not classified for aquatic toxicity.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Tantalum 7440-25-7	-	-	-	-
Niobium (Columbium) 7440-03-1	-	-	-	-
Titanium 7440-32-6	The 72 h EC50 of titanium dioxide to Pseudokirchnerella subcapitata was 61 mg of TiO2/L.	The 96 h LC50 of titanium dioxide to Cyprinodon variegatus was greater than 10,000 mg of TiO2/L. The 96 h LC50 of titanium dioxide to Pimephales promelas was greater than 1,000 mg of TiO2/L.	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of titanium dioxide to Daphnia Magna was greater than 1000 mg of TiO2/L.
Vanadium 7440-62-2	The 72 h EC50 of vanadium pentoxide to Desmodesmus subspicatus was 2,907 ug of V/L.	The 96 h LC50 of vanadium pentoxide to Pimephales promelas was 1,850 ug of V/L.	The 3 h EC50 of sodium metavanadate for activated sludge was greater than 100 mg/L.	The 48 h EC50 of sodium vanadate to Daphnia magna was 2,661 ug of V/L.
Tungsten 7440-33-7	The 72 h EC50 of sodium tungstate to Pseudokirchnerella subcapitata was 31.0 mg of W/L.	The 96 h LC50 of sodium tungstate to Danio rerio was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of sodium tungstate to Daphnia magna was greater than 96 mg of W/L.
Hafnium 7440-58-6	The 72 h EC50 of hafnium to Pseudokirchneriella subcapitata was great than 8 ug of Hf/L (100% saturated solution).	The 96 h LC50 of Hafnium dioxide in water to Danio rerio was greater than the solubility limit of 0.007 mg	-	The 48 h EC50 of Hafnium dioxide to Daphnia magna was greater than the solubility limit of 0.007 mg

#### Other adverse effects

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging None anticipated.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

## 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies

KECLCompliesPICCSNot ListedAICSNot Listed

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

## **US State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Tantalum 7440-25-7	X	X	X
Titanium 7440-32-6	Х		
Vanadium 7440-62-2	X	X	X
Tungsten 7440-33-7	X	X	X
Hafnium 7440-58-6	Х	X	Х

## U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

## **16. OTHER INFORMATION**

NFPA Health hazards 0 Flammability 0 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 1 Flammability 0 Physical hazards 0 Personal protection X

 Issue Date
 28-May-2015

 Revision Date
 23-Apr-2020

**Revision Note** 

Updated Section(s): 1, 3, 4, 5, 9, 12, 15

Note:

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Additional information available Safety

Safety data sheets and labels available at ATImetals.com

from: