SAFETY DATA SHEET

Issue Date 26-Oct-2026 **Revision Date** 26-Oct-2026 **Version** 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Stainless Steel

Other means of identification

Product Code SRP008

Synonyms Stainless Steel: 300-series stainless steels (Fe-Cr-Ni alloys) such as Types 201/201L, Type 301, Type 302, Type 303, Types 304/304L, Type 305, Types 309/309S, Types 310/310S, Type 316/316L, Types 317/317L, Type 321, Type 347, 400-series stainless steels and martensitic stainless steels (Fe-Cr alloys) such as Type 409, Type 410S, Type 439, Type 441, Type 444, FHZ®, Type 412, Type 410, Type 420, Type 440A, Type 418SPL, Duplex stainless steels (DSS) such as DSS 2003, DSS 2304, DSS 2205, DSS 2304, DSS 2507, DSS 255, DSS ZERON® 100Specialty and precipitation-hardening stainless steels such as AL-29-4C® alloy, alloy 219 (21-6-9), alloy 611, alloy 20 (20-CB3) alloy 840™ (Calrod), alloy 332™ (Calrod), alloy 332Mo™, alloy 334 (Calrod), alloy 334Mo™, AL-6XN® alloy, AL-6XNPLUS® alloy, alloy 825, alloy 904L, alloy 50 (XM-19), alloy 60, alloy 31, alloy 15-5 (629), alloy 17-4 (630), alloy 17-7 (631), alloy 15-7 (632), alloy 13-8 (634) alloy AM350, alloy AM355, A-286 alloy, TASSCO CORRHARD, Ohmaloy® 30 alloy, Ohmaloy® 40 alloy, EBRITE® alloy, ALLCOR® alloy, ZeCor™ alloy, SEACURE® alloy, RA 330 alloy

Recommended use of the chemical and restrictions on use

Recommended Use Stainless steel product manufacture.

Uses advised against

Details of the supplier of the safety data sheet

Manufacturer Address

ATI Specialty Rolled Products, 100 River Road, Brackenridge, PA 15014 USA

Emergency telephone number

Company Phone Number ATI SDS Manager: 1-412-225-4911

Emergency Telephone Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article and, as such, does not present a hazard to human health by inhalation or ingestion.

Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Emergency Overview

Danger

Hazard statements

May cause cancer
May cause an allergic skin reaction
Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled
May damage fertility or the unborn child



Appearance Various massive product forms **Physical state** Solid **Odor** Odorless

Precautionary Statements - Prevention
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wear protective gloves

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)
Not applicable
Other Information
When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Zinc, copper, magnesium, or cadmium fumes may cause metal fume fever, Titanium dioxide an IARC Group 2B carcinogen, Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer, Vanadium pentoxide (V_2O_5) affects eyes, skin, respiratory system, Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

Stainless Steel: 300-series stainless steels (Fe-Cr-Ni alloys) such as Types 201/201L, Type 301, Type 302, Type 303, Types 304/304L, Type 305, Types 309/309S, Types 310/310S, Type 316/316L, Types 317/317L, Type 321, Type 347, 400-series stainless steels and martensitic stainless steels (Fe-Cr alloys) such as Type 409, Type 410S, Type 439, Type 441, Type 444, FHZ®, Type 412, Type 410, Type 420, Type 440A, Type 418SPL, Duplex stainless steels (DSS) such as DSS 2003, DSS 2304, DSS 2205, DSS 2304, DSS 2507, DSS 255, DSS ZERON® 100Specialty and precipitation-hardening stainless steels such as AL-29-4C® alloy, alloy 219 (21-6-9), alloy 611, alloy 20 (20-CB3) alloy 840™ (Calrod), alloy 332™ (Calrod), alloy 332Mo™, alloy 334 (Calrod), alloy 334Mo™, AL-6XN® alloy, AL-6XNPLUS® alloy, alloy 825, alloy 904L, alloy 50 (XM-19), alloy 60, alloy 31, alloy 15-5 (629), alloy 17-4 (630), alloy 17-7 (631), alloy 15-7 (632), alloy 13-8 (634) alloy AM350, alloy AM355, A-286 alloy, TASSCO CORRHARD, Ohmaloy® 30 alloy, Ohmaloy® 40 alloy, EBRITE® alloy, ALLCOR® alloy, ZeCor™ alloy, SEACURE® alloy, RA 330 alloy.

Chemical Name	CAS No.	Weight-%
Iron	7439-89-6	< 90
Nickel	7440-02-0	0 - 46
Chromium	7440-47-3	10 - 30
Manganese	7439-96-5	0 - 10

Molybdenum	7439-98-7	0 - 7.0
Silicon	7440-21-3	0 - 6.5
Aluminum	7429-90-5	0 - 4.0
Copper	7440-50-8	0 - 4.0
Tungsten	7440-33-7	0 - 2.5
Titanium	7440-32-6	0 - 2.4
Boron	7440-42-8	0 - 2.25
Vanadium	7440-62-2	0 - 1.1
Tantalum	7440-25-7	0 - 1.0
Niobium (Columbium)	7440-03-1	0 - 1.0
Cobalt	7440-48-4	0 - 0.5

4. FIRST AID MEASURES

First aid measures

Eye contact In the case of particles coming in contact with eyes during processing, treat as with any foreign object.

Skin Contact In the case of skin allergic reactions see a physician.

Inhalation If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove to fresh air and consult a qualified health professional.

Ingestion Not an expected route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl) or class D dry powder fire extinguisher.

Unsuitable extinguishing media Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material.

Specific hazards arising from the chemical

Intense heat. Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Hazardous combustion products Titanium dioxide an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Vanadium pentoxide (V_2O_5) affects eyes, skin, respiratory system. Zinc, copper, magnesium, or cadmium fumes may cause metal fume fever. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters
Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required.

For emergency responders Use personal protective equipment as required.

Environmental precautions

Environmental precautions Not applicable to massive product.

Methods and material for containment and cleaning up

Methods for containment Not applicable to massive product.

Methods for cleaning up Not applicable to massive product.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep chips, turnings, dust, and other small particles away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following:: chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL
Iron 7439-89-6	-	-
Nickel 7440-02-0	TWA: 1.5 mg/m³ inhalable fraction	TWA: 1 mg/m³
Chromium 7440-47-3	TWA: 0.5 mg/m³	TWA: 1 mg/m³
Manganese 7439-96-5	TWA: 0.02 mg/m³ respirable fraction TWA: 0.1 mg/m³ inhalable fraction TWA: 0.02 mg/m³ Mn TWA: 0.1 mg/m³ Mn	(vacated) STEL: 3 mg/m³ fume (vacated) Ceiling: 5 mg/m³ Ceiling: 5 mg/m³ fume Ceiling: 5 mg/m³ Mn
Molybdenum 7439-98-7	TWA: 10 mg/m³ inhalable fraction TWA: 3 mg/m³ respirable fraction	-

Silicon 7440-21-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction
Copper 7440-50-8	TWA: 0.2 mg/m³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m³ fume TWA: 1 mg/m³ dust and mist
Aluminum 7429-90-5	TWA: 1 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction
Tungsten 7440-33-7	STEL: 10 mg/m³ STEL: 10 mg/m³ W TWA: 5 mg/m³ TWA: 5 mg/m³ W	(vacated) STEL: 10 mg/m³ (vacated) STEL: 10 mg/m³ W
Titanium 7440-32-6	-	-
Boron 7440-42-8	-	-
Vanadium 7440-62-2	-	Ceiling: 0.5 mg/m³ V2O5 respirable dust Ceiling: 0.1 mg/m³ V2O5 fume
Tantalum 7440-25-7	-	TWA: 5 mg/m³
Niobium (Columbium) 7440-03-1	-	-
Cobalt 7440-48-4	TWA: 0.02 mg/m³ TWA: 0.02 mg/m³ Co	TWA: 0.1 mg/m³ dust and fume

Appropriate engineering controls

Engineering Controls Avoid generation of uncontrolled particles.

Individual protection measures, such as personal protective equipment

Eye/face protection When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that shield the eyes from particles.

Skin and body protection Wear protective gloves. Fire/flame resistant/retardant clothing may be appropriate during hot work with the product. Cut-resistant gloves and/or protective clothing may be appropriate when sharp surfaces are present.

Respiratory protection When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid		
Appearance	Various massive product forms	**Odor**	Odorless
Color	Metallic gray or silver	**Odor threshold**	Not applicable

Property	**Values**	**Remarks • Method**
pH	-	
Melting point / freezing point	1430-1540 °C / 2600-2800 °F	
Boiling point / boiling range	-	
Flash point	-	
Evaporation rate	-	Not applicable
Flammability (solid, gas)	-	Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product
Flammability Limit in Air		

Upper flammability limit:	-	
Lower flammability limit:	-	
Vapor pressure	-	Not applicable
Vapor density	-	Not applicable
Specific Gravity	7-9	
Water solubility	Insoluble	
Solubility in other solvents	-	
Partition coefficient	-	Not applicable
Autoignition temperature	-	Not applicable
Decomposition temperature	-	Not applicable
Kinematic viscosity	-	Not applicable
Dynamic viscosity	-	Not applicable
Explosive properties	Not applicable	
Oxidizing properties	Not applicable	

Other Information

Softening point	-
Molecular weight	-
VOC Content (%)	Not applicable
Density	-
Bulk density	-

10. STABILITY AND REACTIVITY

Reactivity
Not applicable

Chemical stability
Stable under normal conditions.

Possibility of Hazardous Reactions
None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid
Dust formation and dust accumulation.

Incompatible materials
Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following:: chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

Hazardous Decomposition Products
When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:: Titanium dioxide an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Vanadium pentoxide (V_2O_5) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Not an expected route of exposure for product in massive form.

Eye contact Not an expected route of exposure for product in massive form.

Skin Contact May cause sensitization by skin contact.

Ingestion Not an expected route of exposure for product in massive form.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Iron 7439-89-6	98,600 mg/kg bw	-	> 0.25 mg/L
Nickel 7440-02-0	> 9000 mg/kg bw	-	> 10.2 mg/L
Chromium 7440-47-3	> 3400 mg/kg bw	-	> 5.41 mg/L
Manganese 7439-96-5	>2000 mg/kg bw	-	>5.14 mg/L
Molybdenum 7439-98-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Silicon 7440-21-3	> 5000 mg/kg bw	> 5000 mg/kg bw	> 2.08 mg/L
Copper 7440-50-8	481 mg/kg bw	>2000 mg/kg bw	>5.11 mg/L
Aluminum 7429-90-5	15,900 mg/kg bw	-	> 1 mg/L
Tungsten 7440-33-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Titanium 7440-32-6	> 5000 mg/kg bw	-	-
Boron 7440-42-8	> 2000 mg/kg bw	-	> 5.08 mg/L
Vanadium 7440-62-2	> 2000 mg/kg bw	-	-
Tantalum 7440-25-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Niobium (Columbium) 7440-03-1	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Cobalt 7440-48-4	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L

Information on toxicological effects

Symptoms May cause sensitization by skin contact. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Product not classified.
Skin corrosion/irritation Product not classified.
Serious eye damage/eye irritation Product not classified.
Sensitization May cause sensitization by skin contact. Cobalt-containing alloys may cause sensitization by inhalation.
Germ cell mutagenicity Product not classified.
Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel 7440-02-0		Group 1 Group 2B	Known Reasonably Anticipated	X
Chromium 7440-47-3		Group 3		
Cobalt 7440-48-4	A3	Group 2A Group 2B	Known	X

Reproductive toxicity Contains a known or suspected reproductive toxin.
STOT - single exposure Product not classified.
STOT - repeated exposure Causes disorder and damage to the: Respiratory System.

Aspiration hazard Product not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product as shipped is not classified for aquatic toxicity.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Iron 7439-89-6	-	The 96 h LC50 of 50% iron oxide black in water to Danio rerio was greater than 10,000 mg/L.	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L.	The 48 h EC50 of iron oxide to Daphnia magna was greater than 100 mg/L.
Nickel 7440-02-0	NOEC/EC10 values range from 12.3 µg/l for Scenedesmus accuminatus to 425 µg/l for Pseudokirchneriella subcapitata.	The 96h LC50s values range from 0.4 mg Ni/L for Pimephales promelas to 320 mg Ni/L for Brachydanio rerio.	The 30 min EC50 of nickel for activated sludge was 33 mg Ni/L.	The 48h LC50s values range from 0.013 mg Ni/L for Ceriodaphnia dubia to 4970 mg Ni/L for Daphnia magna.
Chromium 7440-47-3	-	-	-	-
Manganese 7439-96-5	The 72 h EC50 of manganese to Desmodesmus subspicatus was 2.8 mg of Mn/L.	The 96 h LC50 of manganese to Oncorhynchus mykiss was greater than 3.6 mg of Mn/L	The 3 h EC50 of manganese for activated sludge was greater than 1000 mg/L.	The 48 h EC50 of manganese to Daphnia magna was greater than 1.6 mg/L.
Molybdenum 7439-98-7	The 72 h EC50 of sodium molybdate dihydrate to Pseudokirchneriella subcapitata was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to Pimephales promelas was 644.2 mg/L	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to Ceriodaphnia dubia was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to Daphnia magna was greater than 1,727.8 mg/L.
Silicon 7440-21-3	The 72 h EC50 of sodium metasilicate pentahydrate to Pseudokirchnerella subcapitata was greater than 250 mg/L.	-	-	-
Copper 7440-50-8	The 72 h EC50 values of copper chloride to Pseudokirchneriella subcapitata ranged between 30 µg/L (pH 7.02, hardness 250 mg/L CaCO3, DOC 1.95 mg/L) and 824 µg/L (pH 6.22, hardness 100 mg/L CaCO3, DOC 15.8 mg/L).	The 96-hr LC50 for Pimephales promelas exposed to Copper sulfate ranged from 256.2 to 38.4 ug/L with water hardness increasing from 45 to 255.7 mg/L.	The 24 h NOEC of copper chloride for activated sludge ranged from 0.32 to 0.64 mg of Cu/L.	The 48 h LC50 values for Daphnia magna exposed to copper in natural water ranged between 33.8 µg/L (pH 6.1, hardness 12.4 mg/L CaCO3, DOC 2.34 mg/L) and 792 µg/L (pH 7.35, hardness 139.7 mg/L CaCO3, DOC 22.8 mg/L).
Aluminum 7429-90-5	The 96-h EC50 values for reduction of biomass of Pseudokirchneriella subcapitata in AAP-Medium at pH 6, 7, and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved Al.	The 96 h LC50 of aluminum to Oncorhynchus mykiss was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH 7.5	-	The 48-hr LC50 for Ceriodaphnia dubia exposed to Aluminium chloride increased from 0.72 to greater than 99.6 mg/L with water hardness increasing from 25 to 200 mg/L.
Tungsten 7440-33-7	The 72 h EC50 of sodium tungstate to Pseudokirchnerella subcapitata was 31.0 mg of W/L.	The 96 h LC50 of sodium tungstate to Danio rerio was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of sodium tungstate to Daphnia magna was greater than 96 mg of W/L.
Titanium 7440-32-6	The 72 h EC50 of titanium dioxide to Pseudokirchnerella	The 96 h LC50 of titanium dioxide to Cyprinodon variegatus was greater than	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000	The 48 h EC50 of titanium dioxide to Daphnia Magna was greater than 1000 mg of

	subcapitata was 61 mg of TiO2/L.	10,000 mg of TiO2/L. The 96 h LC50 of titanium dioxide to Pimephales promelas was greater than 1,000 mg of TiO2/L .	mg/L.	TiO2/L.
Boron 7440-42-8	The 72-h EC50 value for reduction of biomass of Pseudokirchneriella subcapitata exposed to Boric acid at pH 7.5 to 8.3 was 40.2 mg/L.	The 96-hr LC50 for Pimephales promelas exposed to Boric acid (82%)/borax (18%) mixture was 79.7 mg/L with water hardness of 91 mg/L and water pH of 8.0.	The 3 h NOEC of boric acid for activated sludge ranged from 17.5 to 20 mg/L.	The 48-hr LC50 for Ceriodaphnia dubia exposed to Boric acid/borax mixture ranged from 91 to 165 mg/L with pH ranging from 6.7 to 8.4.
Vanadium 7440-62-2	The 72 h EC50 of vanadium pentoxide to Desmodesmus subspicatus was 2,907 ug of V/L.	The 96 h LC50 of vanadium pentoxide to Pimephales promelas was 1,850 ug of V/L .	The 3 h EC50 of sodium metavanadate for activated sludge was greater than 100 mg/L.	The 48 h EC50 of sodium vanadate to Daphnia magna was 2,661 ug of V/L.
Tantalum 7440-25-7	-	-	-	-
Niobium (Columbium) 7440-03-1	-	-	-	-
Cobalt 7440-48-4	The 72 h EC50 of cobalt dichloride to Pseudokirchneriella subcapitata was 144 ug of Co/L.	The 96h LC50 of cobalt dichloride ranged from 1.5 mg Co/L for Oncorhynchus mykiss to 85 mg Co/L for Danio rerio.	The 3 h EC50 of cobalt dichloride for activated sludge was 120 mg of Co/L.	The 48 h LC50 of cobalt dichloride ranged from 0.61 mg Co/L for Ceriodaphnia dubia tested in soft, DOM-free water to >1800mg Co/L for Tubifex tubifex in very hard water.

Persistence and degradability

Bioaccumulation

Other adverse effects This product as shipped is not classified for environmental endpoints. However, when subjected to sawing or grinding, particles may be generated that are classified for aquatic chronic toxicity.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging None anticipated.

Chemical Name	RCRA - D Series Wastes
Chromium 7440-47-3	5.0 mg/L regulatory level

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Not Listed
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372: Chromium (Cr)

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Nickel - 7440-02-0	7440-02-0	0 - 46	0.1
Chromium - 7440-47-3	7440-47-3	10 - 30	1.0
Manganese - 7439-96-5	7439-96-5	0 - 10	1.0
Copper - 7440-50-8	7440-50-8	0 - 4.0	1.0
Cobalt - 7440-48-4	7440-48-4	0 - 0.5	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nickel 7440-02-0		X	X	
Chromium 7440-47-3		X	X	
Copper 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs
Nickel 7440-02-0	100 lb
Chromium	5000 lb

7440-47-3	
Copper 7440-50-8	5000 lb

US State Regulations

California Proposition 65

This product contains the Proposition 65 chemicals listed below. Proposition 65 warning label available at ATImaterials.com.

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen
Cobalt - 7440-48-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Nickel 7440-02-0	X	X	X
Chromium 7440-47-3	X	X	X
Manganese 7439-96-5	X	X	X
Molybdenum 7439-98-7	X	X	X
Silicon 7440-21-3	X	X	X
Copper 7440-50-8	X	X	X
Aluminum 7429-90-5	X	X	X
Tungsten 7440-33-7	X	X	X
Titanium 7440-32-6	X		
Vanadium 7440-62-2	X	X	X
Tantalum 7440-25-7	X	X	X
Cobalt 7440-48-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA **Health hazards** 1 **Flammability** 0 **Instability** 0 **Physical and Chemical Properties** -

HMIS **Health hazards** 2* **Flammability** 0 **Physical hazards** 0 **Personal protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Issue Date 26-Oct-2026
Revision Date 26-Oct-2026
Revision Note
Based on SDS FRP008: Updated Section(s): 1, 2, 3, 8, 9, 11

Note:

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Additional information available from:	Safety data sheets and labels available at ATImaterials.com